

تعداد	مدل	تصویر	خصوصیات	قیمت (تومان)
1	VM-430BX		FIXED 4MP AHD IR BULLET CAMERA 2MP resolution (1920*1080), 25fps 3.6 mm lens, 0 lux IR on Max IR distance: 30 meters OSD Menu, DWDR, D&N, 2DDNR DC12V, IP66	ناموجود
1	VM-250BL		FIXED 2MP AHD IR BULLET CAMERA 2MP resolution (1920*1080), 25fps 3.6 mm lens, 0 lux IR on Max IR distance: 40 meters OSD Menu, DWDR, D&N, 2DDNR DC12V, IP66	430,000
2	VM-230BL		FIXED 2MP AHD IR BULLET CAMERA 2MP resolution (1920*1080), 25fps 3.6 mm lens, 0 lux IR on Max IR distance: 20 meters OSD Menu, DWDR, D&N, 2DDNR DC12V, IP66	360,000
3	VM-230BN		FIXED 2MP AHD IR BULLET CAMERA 2MP resolution (1920*1080), 25fps 3.6 mm lens, 0 lux IR on Max IR distance: 20 meters OSD Menu, DWDR, D&N, 2DDNR DC12V, IP66	355,000
4	VM-230BP		FIXED 2MP AHD IR BULLET CAMERA 2MP resolution (1920*1080), 25fps 3.6 mm lens, 0 lux IR on Max IR distance: 20 meters OSD Menu, DWDR, D&N, 2DDNR DC12V, IP66	365,000
5	VM-230BS		FIXED 2MP AHD IR DOME CAMERA 2MP resolution (1920*1080), 25fps 3.6 mm lens, 0 lux IR on Max IR distance: 30 meters OSD Menu, DWDR, D&N, 2DDNR DC12V, IP66	370,000
5	VM-230D		FIXED 2MP AHD IR DOME CAMERA 2MP resolution (1920*1080), 25fps 3.6 mm lens, 0 lux IR on Max IR distance: 20 meters OSD Menu, DWDR, D&N, 2DDNR DC12V, IP66	365,000
6	VM-1004L		4 CHANNEL 1080N Support Support 4CH 1080N @ 25f/s Support AHD/HDTVI/HDCVI/XVI/IP/analog camera IP camera support in NVR mode H.264 encoding compression 4 CH sync real time playback HDMI, VGA (1280x1024), CVBS Support 1 SATA (6TB) & 2*USB 2.0 Support 4/1 Audio I/O, two way talk RS-485, wifi dongle, RJ45 (100M) Network monitoring by web viewer, Xmeye, P2P	720,000

7	VM-1008L 	8 CHANNEL 1080N Support 8CH 1080N @ 12f/s Support AHD/HDTV/HDCVI/XVI/IP/analog camera IP camera support in NVR mode H.264 encoding compression 8 CH sync real time playback HDMI , VGA (1280x1024), CVBS Support 1SATA (6TB) & 2*USB 2.0 Support 4/1 Audio I/O , two way talk RS-485, wifi dongle , RJ45 (100M) Network monitoring by web viewer, Xmeye, P2P	960,000
8	VM-1016L 	16 CHANNEL 1080N Support 16CH 1080N @ 15f/s Support AHD/HDTV/HDCVI/XVI/IP/analog camera IP camera support in NVR mode H.265 encoding compression 16 CH sync real time playback HDMI , VGA (1920*1080p), CVBS Support 2 SATA (12TB) & 2*USB 2.0 Support 2/1 Audio I/O , two way talk RS-485, wifi dongle , RJ45 (100M) Network monitoring by web viewer, Xmeye, P2P	1,615,000
8	VM-3004L 	4 CHANNEL 1080N Support 4ch 1080Punreal-time encoding Support AHD/HDTV/HDCVI/XVI/IP/analog camera Support 4ch 5M-N@12fps (6 in 1) / 4ch 4M-N@15fps (6 in 1) ,default 5M-N IP camera support in NVR mode H.265X/H.264 encoding compression 4 CH sync real time playback HDMI , VGA (1920*1080p) Support 1 SATA (8TB) & 2*USB 2.0 Support 1/1 Audio I/O , two way talk RS-485, 3G, wifi dongle , RJ45 (100M) Network monitoring by web viewer, VMS, Hi-view, P2P	ناموجود
8	VM-3008L 	8CHANNEL 1080N Support 8ch 5M-Nunreal-time encoding Support AHD/HDTV/HDCVI/XVI/IP/analog camera Support 8ch5M-N@12fps (6 in 1) / 8ch4M-N@15fps (6 in 1) ,default5M-N IP camera support in NVR mode H.265+/H.265/H.264 encoding compression 8 CH sync real time playback HDMI , VGA (1920*1080p) Support 2SATA (8TB) & 2*USB 2.0 Support 1/1 Audio I/O , two way talk RS-485, 3G, wifi dongle , RJ45 (100M) Network monitoring by web viewer, VMS, Hi-view, P2P	ناموجود
8	VM-3016L 	16 CHANNEL 1080N Support 16ch 5M-Nunreal-time encoding; Support AHD/HDTV/HDCVI/XVI/IP/analog camera Support16ch5M-N@12fps(6 in 1)/16ch 4M-N@15fps(6 in 1)/16ch 1080N@15fps(6 in 1), default 5M-N IP camera support in NVR mode H.265+/H.265/H.264 encoding compression 8 CH sync real time playback HDMI , VGA (1920*1080p) Support 2 SATA (8TB) & 2*USB 2.0 Support 2/1 Audio I/O , two way talk RS-485, 3G, wifi dongle , RJ45 (100M) Network monitoring by web viewer, VMS, Hi-view, P2P	ناموجود