دوربين تحت شبكه - HIKVISION NVR			
مدل	اطلاعات محصول	قیمت (ریال)	تصوير محصول
	ColorVu Series		
DS-2CD1047G0-L	4 MP ColorVu Fixed Mini Bullet Network Camera High quality imaging with 4 MP resolution 24/7 full color imaging Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials	48,590,000	
DS-2CD1057G0-L	5 MP ColorVu Fixed Mini Bullet Network Camera High quality imaging with 4 MP resolution 24/7 full color imaging Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials	52,030,000	02 02
DS-2CD2027G2-L	High quality imaging with 2 MP resolution 24/7 full color imaging Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials	62,850,000	
DS-2CD2126G2-ISU	High quality imaging with 2 MP resolution Excellent low-light performance with powered-by- DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle classification based on deep learning -SU: Built-in microphone for real-time audio security, Audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)	72,130,000	in tools
DS-2CD2047G2-L	High quality imaging with 4 MP resolution 24/7 full color imaging Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials	68,760,000	
DS-2CD2087G2-L	High quality imaging with 8 MP resolution 24/7 full color imaging Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials Bulit in Mic	138,490,000	

DS-2CD1347G0-L	High quality imaging with 4 MP resolution Excellent low-light performance Efficient H.265+ compression technology Water and dust resistant (IP67) 24/7 colorful imaging WDR,BLC, HLC, 3D DNR	72,230,000	mar ISON
DS-2CD1357G0-L	High quality imaging with 5 MP resolution Excellent low-light performance Efficient H.265+ compression technology Water and dust resistant (IP67) 24/7 colorful imaging WDR,BLC, HLC, 3D DNR	52,010,000	antigone (S)
DS-2CD1327G0-L	2 MP ColorVu Fixed Turret Network Camera High quality imaging with 2 MP resolution Excellent low-light performance Efficient H.265+ compression technology Water and dust resistant (IP67) 24/7 colorful imaging/Digital WDR	Call	Inter
DS-2CD2347G2-L	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)	69,800,000	instra Instra
DS-2CD2347G2-LU	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)	79,410,000	June -
DS-2CD2T66G2-4I	High quality imaging with 6 MP resolution Excellent low-light performance with powered-by- DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)	78,940,000	and the
DS-2CD2T86G2-4I	High quality imaging with 8 MP resolution Excellent low-light performance with powered-by- DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light by 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)	107,470,000	

DS-2CD2T87G2-LK	High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 130 dB WDR technology Focus on human and vehicle classification based on deep learning 24/7 colorful imaging t. In zero-light scenarios, built-in, warm supplemental lighting works to guarantee colorful images.	113,860,000	
	Lite Mini Bullet Series		
DS-2CD1023G0E-I	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting thanks to DWDR technology Water- and dust- resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range.	25,560,000	
DS-2CD1023G0-I	 2.0 MP IR Network Bullet Camera-2 1/2.8" progressive scan CMOS 2 3D DNR (Digital Noise Reduction)2 1920 × 1080@30fps 2 Up to 30 m IR range 2.8 mm/4 mm/6 mm fixed lens 2 PoE (Power over Ethernet) 2 H.265+, H.265, H.264+, H.264 2 IP672 Dual stream2 	Call	
DS-2CD1023G0-IUF	high quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range Support up to 256 GB SD card storage Built-in microphone for real-time audio security	36,070,000	annon -
DS-2CV1021G0- IDW1	1/2.8" progressive scan CMOS,Up to 30 m IR range 1920 × 1 0 80 30 fps , B uilt in m icro SD/SDHC/SDXC slot, up to128G 2.8/4 mm fixed lens, Built in Wi Fi Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON),Mobile m onitoring via Hik Connect, 3D DNR, IP66	Call	nun QU
DS-2CD1043G0-I	4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps ☑ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ☑ PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, (Wide Dynamic Range)	37,430,000	
DS-2CD1053G0-I	5.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps ☑ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ☑ PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, (Wide Dynamic Range)	Call	

DS-2CD1043G0E-I	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light with 120 dB WDR Water and dust resistant (IP67) EXIR 2.0, advanced infrared technology with long IR distance	Call	annan -
	Lite Dome Series		
DS-2CD1123G0-I	IP67, 2MP dome Exir, fixed lens 2.8mm,white color- 1/2.8" progressive scan CMOS 2 3D DNR (Digital Noise Reduction) 2 1920 × 1080@30fps 2 Up to 30 m IR range2 2.8 mm/4 mm/6 mm fixed lens 2 PoE (Power over Ethernet)2 H.265+, H.265, H.264+, H.264 2 IP67, IK102 Dual stream2 Digital WDR (Wide Dynamic Range)	Call	INCUSSION
DS-2CD1123G0E-I	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting thanks to DWDR technology Water- and dust- resistant (IP67), vandal proof (IK10)	26,470,000	JAK VASAV
DS-2CD1323G0E-I	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	26,180,000	instea
DS-2CD1323G0-IUF	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range Built-in microphone for real-time audio security Support up to 256 GB SD card storage	31,770,000	rentrant
DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS 2 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps 2 Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 2 IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	41,990,000	ANY FROM
DS-2CD1143G0-IUF	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) and vandal resistant (IK10) EXIR 2.0: advanced infrared technology with long IR range Support up to 256 GB SD card storage Built-in microphone for real-time audio security	49,520,000	JAN YELDY

P			
DS-2CD1153G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS 2 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps 2 Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 2 IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	48,250,000	ANY YEAR
DS-2CD1353G0-I	5MP Fixed Turret Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range	52,050,000	PIRKING.
	Mini Bullet Series		
DS-2CD2023G2-I	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)	Call	
DS-2CD2021G1-I	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Support up to 256 GB SD card storage	44,210,000	ann
DS-2CD2043G2-IU	High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology -U: Built-in microphone for real-time audio security Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning	69,980,000	
DS-2CD2043G2-I	High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning	58,790,000	Altro Cat
DS-2CD2052-I	 1/3" Progressive CMOS, ICR, Olux with IR, 2560×1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & POE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service 	Call	voice

DS-2CD2063G0-I	6 MP IR Fixed Bullet Network Camera -2 1/2.9" Progressive Scan CMOS 2 3072 × 2048@20 fps 2 2.8/4/6/8 mm fixed lens 2 Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR 2 H.265+, H.265, H.264+, H.264 2 Behavior analyses 2 120dB WDR -2 BLC/3D DNR/ROI 2 IP67 2 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	Call	
DS-2CD2063G2-I	High quality imaging with 6 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning	64,400,000	AUGO DE
DS-2CD2083G2-I	High quality imaging with 8 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning	Call	
DS-2CD2083G0-I	8 MP IR Fixed Bullet Network Camera -2 1/2.5" Progressive Scan CMOS 2 3840 × 2160 @15 fps 2 2.8/4/6/8 mm fixed lens 2 Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR 2 H.265+, H.265, H.264+, H.264 2 2 Behavior analyses 2 120dB WDR -2 BLC/3D DNR/ROI/HLC 2 IP67 2 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	Call	
	Dome Series		
DS-2CD2123G2-I	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning -S: audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)	49,130,000	HIGHTON
DS-2CD2143G2-IU	4 MP Vandal Built-in Mic Fixed Dome Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning	52,710,000	HIRTHSON

DS-2CD2143G0-IS (Black)	4 MP IR Fixed Dome Network Camera 1/3" Progressive Scan CMOS, 2688 ×1520@30fps, 2.8/4/6/8mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI, IP67,IK10, Built-in micro SD/SDHC/SDXC card slot, up to 128 GB, 3-Axis adjustment	Call	HIKVISSION
DS-2CD2143G0-IU	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Built-in microphone for real-time audio security Water and dust resistant (IP66) and vandal proof (IK10) Robust structure design with full metal materials	Call	autor
DS-2CD2163G0-I(S) (BLACK)	6 MP IR Fixed Dome Network Camera - 2 1/2.9" Progressive Scan CMOS 2 3072 × 2048@20 fps 2 2.8/4/6/8 mm fixed lens 2 Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR 2 H.265+, H.265, H.264+, H.264 2 2 Behavior analyses 2 120dB WDR - 2 BLC/3D DNR/ROI 2 IP67 2 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	Call	HIKVISION
DS-2CD2163G0-IU	6 MP WDR Fixed Dome Network Camera with Build-in Mic High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Built-in microphone for real-time audio security Water and dust resistant (IP66) and vandal proof (IK10) Robust structure design with full metal materials	Call	ADVICES -
DS-2CD2183G2-IU	8 MP Vandal Built-in Mic Fixed Dome Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning	Call	Anican CO
DS-2CD2183G0-IS	8 MP IR Fixed Dome Network Camera - 2 1/2.9" Progressive Scan CMOS 2 3072 × 2048@20 fps 2 2.8/4/6/8 mm fixed lens 2 Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR 2 H.265+, H.265, H.264+, H.264 2 2 Behavior analyses 2 120dB WDR - 2 BLC/3D DNR/ROI 2 IP67 2 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	Call	HEIGH HEIGH

DS-2CD2183G0-IS (Black)	8 MP IR Fixed Dome Network Camera -2 1/2.9" Progressive Scan CMOS 2 3072 × 2048@20 fps 2 2.8/4/6/8 mm fixed lens 2 Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR 2 H.265+, H.265, H.264+, H.264 2 Behavior analyses 2 120dB WDR -2 BLC/3D DNR/ROI 2 IP67 2 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	Call	никизын
	Bullet Series		
DS-2CD2T43G0-I5	 1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI,IP67,Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range 	Call	
DS-2CD2T43G0-18	 1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI,IP67,Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range 	Call	
DS-2CD2T43G2-2I	High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning Up to 60M IR	71,370,000	
DS-2CD2T43G2-4I	High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning Up to 80M IR	69,670,000	
DS-2CD2T63G0-I5	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI DP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS D 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens D Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR DH.265+, H.265, H.264+, H.264 D 2 Behavior analyses D120dB WDR	Call	
DS-2CD2T63G0-18	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS I 3072 × 2048@20 fps I 2.8/4/6/8 mm fixed lens I Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR I H.265+, H.265, H.264+, H.264 I 2 Behavior analyses I 120dB WDR - up to 80m IR range	Call	

DS-2CD2T63G2-4I	High quality imaging with 6 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning Up to 80M IR	Call	
DS-2CD2T83G0-I5	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens I Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR I H.265+, H.265, H.264+, H.264 I 2 Behavior analyses I 120dB WDR .I BLC/3D DNR/ROI I IP67 I Built-in micro SD/SDHC/SDXC card slot, up to 128 G	Call	
DS-2CD2T83G2-4I	High quality imaging with 8 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning Up to 80M IR	Call	
DS-2CD2T83G0-18	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens 2 Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR 2 H.265+, H.265, H.264+, H.264 2 2 Behavior analyses 2 120dB WDR 2 BLC/3D DNR/ROI 2 IP67 2 Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	Call	
	Lite Bullet Vari-Facal Motorized Series		
DS-2CD1623G0-I	Hikvision DS-2CD1623G0-I 2MP (1920 × 1080) Vari- focal IR Bullet Network Camera SPECIFICATIONS2MP HD1080P 1/2.8" Progressive Scan CMOS1920 × 1080@30fps (N)2.8~12mm VF lens IR range: Up to 30m	Call	
DS-2CD1623G0-IZ	S-2CD1623GO-IZ Bullet Network camera 2MP, 2.8- 12mm varifocal lens, EXIR, microSD1/2.8" progressive scan CMOSBLC/3D DNR/ROI1920 × 1080@30fps Up to 30 m IR rangeIP672.8 mm to 12 mm varifocal lensDigital WDRH.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 LuxBuilt-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	Call	
DS-2CD1643G0-I	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS ID BLC/3D DNR/ROI, 2560 × 1440@20fps, Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens, IP67, H.265+, H.265, H.264+, H.264 ID 120 dB WDR, Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), Built-in micro SD/SDHC/SDXC card slot,up to 128 GB	Call	

DS-2CD1643G0-IZ	 I/3" progressive scan CMOS I BLC/3D DNR/ROI 2560 × 1440@20fps I Up to 30 m IR range 2.8 mm to 12 mm varifocal motorize lens I IP67 H.265+, H.265, H.264+, H.264 I 120 dB WDR Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 	71,970,000	
	Lite Dome Vari-Facal Motorize Series		
DS-2CD1723G0-I	 1/2.8" progressive scan CMOS 2 3D DNR (Digital Noise Reduction) 2 1920 × 1080@30fps 2 Up to 30 m IR range 2 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens 2 PoE (Power over Ethernet) 2 IP67, IK10 H.265+, H.265, H.264+, H.264 2 Dual stream 2 Digital WDR (Wide Dynamic Range) 	Call	IN THEM
DS-2CD1743G0-IZ	1/3" progressive scan CMOS I 3D DNR (Digital Noise Reduction)/ 2560 × 1440@20fps I Up to 30 m IR range 2.8 mm to 12 mm manual/motorized (with-Z) vari-focal lens PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264 Dual stream 120 dB WDR (Wide Dynamic Range)	80,800,000	In the second seco
DS-2CD1753G0-IZ	1/3" progressive scan CMOS I∂ 3D DNR (Digital Noise Reduction)/ 2560 × 1440@20fps I∂ Up to 30 m IR range 2.8 mm to 12 mm manual/motorized (with-Z) vari-focal lens PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264 Dual stream 120 dB WDR (Wide Dynamic Range)	98,470,000	IN STATE
DS-2CD1743G0-I	4.0 MP VF Network Bullet Camera, 1/3" progressive scan CMOS 2 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps 2 Up to 30 m IR range, 2.8 mm to 12 mm manual/motorized (with-Z) vari-focal lens, PoE (Power over Ethernet), IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB WDR (Wide Dynamic Range)	Call	* 105000 *
	Bullet Vari-Facal Motorized Series 4 MP WDR Motorized Varifocal Bullet Network		
DS-2CD2643G2-IZS	Camera High quality imaging with 4 MP resolution Motorized varifocal lens for easy installation and monitoring Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning	110,320,000	

DS-2CD2663G0-IZS DS-2CD2683G2-IZS	 BLC/3D DNR/ROI I IP67, IK10 I Built-in micro SD/SDHC/SDXC card slot, up to 128 GB I 1/2.9" Progressive Scan CMOS I 3072 × 2048@20 fps I 2.8 to 12 mm varifocal lens I Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR I H.265+, H.265, H.264+, H.264 I 2 Behavior analyses - Z:Motorized VF lens 8 MP(4K) IR Vari-focal Bullet Network Camera-• 1/2.5" Progressive Scan CMOS • 3840 ×2160@15fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D 	Call	
	DNR/ROI • IP67, IK10 - Z:Motorized VF lens		
	Dome Vari-Facal Motorized Series		
DS-2CD2743G2-IZS	4 MP IR VF Dome Network Camera - BLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment 1/3" Progressive Scan CMOS 22560 × 1440@30fps 2 2.8 to 12 mm Varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 I Three streams 1 120dB WDR 2 behavior analyses, and face detection - WDR-Day & Night IR Cut Filter Digital Noise Reduction 3D DNR - Z: Motorized VF lens	117,440,000	
DS-2CD2763G1-IZS	 4 MP IR VF Dome Network Camera - BLC/3D DNR/ROI DIP67, IK10 Disuit-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment 1/3" Progressive Scan CMOS 2560 × 1440@30fps 2 2.8 to 12 mm Varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR 1.265+, H.265+, H.264+, H.264 Distribution Three streams 120dB WDR 2 behavior analyses, and face detection - WDR-Day & Night IR Cut Filter Digital Noise Reduction 3D DNR - Z: Motorized VF lens 	142,160,000	
DS-2CD2783G0-IZS	 8 MP(4K) IR Vari-focal Dome Network Camera • 1/2.5" Progressive Scan CMOS • 3840 ×2160@15fps • 2.8 to 12 mm varifocal lens• Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detectio • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens 	Call	ADDODY

DS-2CD2786G2-IZS	High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP66) and vandal proof (IK10)	173,360,000	ALL DAYS
	Fish Eye Series		
DS-2CD2942F-IS	Color: 0.01lux @(F1.2, AGC ON), 0.018lux @(F1.6, AGC ON), 0 lux with IR 2560 × 1440 1.6mm, F1.6 Angle of view: 186°(horizontal), 106°(vertical) H.264/MJPEG 50Hz: 12.5fps(2560 × 1440), 25fps(1920 × 1080, 1280 × 720) 60Hz: 15fps(2560 × 1440), 30fps(1920 × 1080, 1280 × 720) 8 meters 12 VDC ± 10%, PoE (802.3af)	Call	ACCESS OF A
DS-2CD2955FWD-IS	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 × 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & POE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	126,380,000	
	Cube Smart Series		
DS-2CD2421G0-IW	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Provides real-time security via built-in two-way audio Detects human body through passive infrared is sensitive to body temperature (PIR) -W: Wi-Fi connection -D: DC power supply	Call	
DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built- in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR	Call	
DS-2CD2443G0-IW	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams,DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to10m, support on-board storage up to 128GB(SD card not included), built-in WIFI	Call	

DS-2DE4225IW-DE S6	1/2.8" progressive scan CMOS High quality imaging with 2 MP resolution Excellent low-light performance with powered-by- DarkFighter technology 25× optical zoom and 16× digital zoom provide close up views over expansive areas WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression	196,840,000	
DS-2DE4225IW-DE T5	Focuses on human and vehicle targets classification based on deep learning Support face capture. Up to 5 faces captured at the same time 1/2.8" progressive scan CMOS High quality imaging with 2 MP resolution Excellent low-light performance with powered-by- DarkFighter technology 25× optical zoom and 16× digital zoom provide close up views over expansive areas Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression	Call	
DS-2DE4425IW-DE T5	Focuses on human and vehicle targets classification based on deep learning Support face capture. Up to 5 faces captured at the same time 1/2.8" progressive scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by- DarkFighter technology 25× optical zoom and 16× digital zoom provide close up views over expansive areas Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression	223,060,000	
DS-2DE5220IW-DE	 1/2.8" Progressive Scan CMOS Up to 2048 x 1536 Resolution 30× Optical Zoom, 16× Digital Zoom IR Distance up to 492 ft (150 m) Digital WDR 3D Intelligent Positioning Function Support for H.265+/H.265 Video Compression IP66, IK10 24 VAC/Hi-PoE (injector supplied), 32 W 	288,600,000	IR VEGOV
DS-2DE4425IW-DE	High quality imaging with 4 MP resolution DarkFighter technology Clear imaging against strong back lighting due to 120 dB WDR technology Pan and tilt ability enables camera to monitor zones of interest 25x optical zoom allows for closer viewing of subjects in expansive areas Up to 100m IR range ensures safety at night Water and dust resistant (IP66)	Call	
DS-2DE4A320IW-DE	 1/2.8" Progressive Scan CMOS Up to 2048 × 1536 resolution 20× Optical Zoom, 16× Digital Zoom WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance 12 VDC & PoE+ (802.3at, class4) Support H.265 video compression 	Call	

	NVR 4 Channel		
DS-7104NI-Q1/M	Incoming bandwidth: 40Mbps - P video input: 4-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	Call	
DS-7104NI-Q1/4P/M	Incoming bandwidth: 40Mbps - P video input: 4-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	Call	
DS-7604NI-Q1	IP video input 4-ch,Up to 8 MP resolution,Incoming bandwidth 40 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,	Call	
DS-7604NI-Q1/4P	IP video input 4-ch,Up to 8 MP resolution,Incoming bandwidth 40 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk, 4 independent PoE network interfaces	Call	-
DS-7604NI-K1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	54,460,000	
DS-7604NI-K1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	Call	
	NVR 8 Channel		
DS-7108NI-Q1/M	Incoming bandwidth: 60Mbps - P video input: 8-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	43,690,000	
DS-7108NI-Q1/8P/M	Incoming bandwidth: 60Mbps - P video input: 8-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	Call	

DS-7608NI-Q1	IP video input 8-ch,Up to 8 MP resolution,Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,	Call	
DS-7608NI-K1/8P	Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth 8 independent PoE network interfaces 1 self-adaptive 10/100 Mbps Ethernet interface	Call	199 a
DS-7608NI-Q2	sales, [05.01.19 11:19] IP video input 8-ch, Up to 8 MP resolution, Incoming bandwidth: 80 Mbps,Outgoing bandwidth: 80 Mbps, 2 SATA interfaces,Two-way audio	61,800,000	10 0
DS-7608NI-K1	80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	60,450,000	
DS-7608NI-Q2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	Call	
	NVR 16 Channel		
DS-7616NI-Q1	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 1 SATA interfaces ,Two- way audio 1-ch	Call	
DS-7616NI-Q2/16P	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 2 SATA interfaces ,Two- way audio 1-ch, 16 independent PoE network interfaces	Call	
DS-7616NI-Q2	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 1 SATA interfaces ,Two- way audio 1-ch	79,440,000	
DS-7616NI-K2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	83,360,000	
DS-7716NI-K4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	Call	

DS-7716NI-Q4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	157,550,000	44 AN A T
DS-7716NI-Q4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	225,700,000	
	NVR 32 Channel		
ds-7732ni-K4	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	186,050,000	
DS-7732NI-K4/16P	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	295,730,000	44 A
DS-7732NI-Q4	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	Call	- 44464
DS-7732NI-Q4/16P	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	Call	44-544
DS-9632NI-18	Up to 32 channel IP cameras can be connected Up to 12 MP high-definition live view, storage and playback Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	626,320,000	·····································