





































مدل	اطلاعات محصول	قیمت (ریال)	تصویر محصول
Turbo HD - 2&1MP ColorVu			
DS-2CE10DFT-F	<p>2 MP full time color bullet camera 24/7 full color imaging Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS);</p>	Call	
DS-2CE12DF3T-FS	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67) High quality audio with audio over coaxial cable, built-in mic</p>	33,910,000	
DS-2CE10DF3T-FS	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm fixed focal lens Up to 20 m white light distance for bright night imaging High quality audio with audio over coaxial cable, built-in mic One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	25,690,000	
DS-2CE72DF3T-F	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	22,480,000	
DS-2CE70DFT-PF	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Up to 20 m white light distance for bright night imaging High quality audio with audio over coaxial cable, built-in mic One port for four switchable signals (TVI/AHD/CVI/CVBS)</p>	Call	
DS-2CE70DF0T-PF	<p>2 MP ColorVu Indoor Fixed Turret Camera High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture 3D DNR technology delivers clean and sharp images Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) DWDR;BLC;HLC;Global</p>	20,730,000	
Turbo HD - 2MP			
DS-2CE16D0T-EXIF	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)</p>	11,480,000	





DS-2CE16D0T-EXIPF	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)</p>	Call	
DS-2CE16D0T-ITPF	<p>2 MP, 1920 × 1080 resolution 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) Smart IR, up to 25 m IR distance IP67</p>	7,920,000	
DS-2CE16D0T-ITPFS	<p>2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 25 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	14,500,000	
DS-2CE16D0T-ITF	<p>2 MP Fixed Mini Bullet Camera 2 MP bullet camera Smart IR: up to 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	Call	
DS-2CE16D3T-ITF	<p>2 MP bullet camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	19,160,000	
DS-2CE16D0T-ITFS	<p>2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) DWDR/BLC/HLC/Global</p>	15,590,000	
DS-2CE17D0T-IT1F	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	15,970,000	
DS-2CE17D0T-IT3F	<p>High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)</p>	20,490,000	
DS-2CE76D3T-ITPF	<p>2 MP Ultra Low Light Indoor Fixed Turret Camera 2 MP turret camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).</p>	15,410,000	
DS-2CE76D0T-ITMF	<p>2 MP, 1920 × 1080 resolution DWDR/BLC/HLC/Global 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) Smart IR, up to 30 m IR distance IP67</p>	14,550,000	

DS-2CE76D0T-EXIPF	High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS)	11,850,000	
DS-2CE76D0T-ITPF	2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) Smart IR, up to 20 m IR distance	9,950,000	
DS-2CE76D0T-ITMFS	2 MP, 1920 × 1080 resolution DWDR/BLC/HLC/Global up to 30 m IR distance Audio over coaxial cable, built-in mic 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67	16,640,000	
DS-2CE76D0T-ITPFS	2 MP Audio Indoor Fixed Turret Camera 2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	13,120,000	
DS-2CE78D0T-IT3FS	2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	21,090,000	
2MP VariFocal			
DS-2CE16D0T-VFIR3F	2 megapixel highperformance CMOS Analog HD output, up to 1080p resolution Day/Night switch Smart IR Up to 40m IR distance Switchable TVI/AHD/CVI/CVBS IP66-Lens 2.8 - 12 mm @ F1.4, Switchable TVI/AHD/CVI/CVBS	28,780,000	
DS-2CE56D0T-VFIR3F	2 megapixel highperformance CMOS Analog HD output, up to 1080p resolution Day/Night switch Smart IR Up to 40m IR distance Switchable TVI/AHD/CVI/CVBS IP66-Lens 2.8 - 12 mm @ F1.4, Switchable TVI/AHD/CVI/CVBS	28,520,000	
Turbo HD - 5MP			
DS-2CE16H0T-ITF	5 MP Bullet Camera • 5 Megapixel high-performance CMOS • Analog HD output, up to 5MP resolution • True Day/Night • OSD menu, 2D DNR, DWDR • EXIR technology, up to 20m IR distance • IP67 • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) • Up the Coax(HIKVISION-C)	17,220,000	
DS-2CE16H0T-ITPF	5 MP Bullet Camera • 5 Megapixel high-performance CMOS • Analog HD output, up to 5MP resolution • True Day/Night • OSD menu, 2D DNR, DWDR • EXIR technology, up to 20m IR distance • IP67 • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) • Up the Coax(HIKVISION-C)	15,690,000	
DS-2CE16H0T-ITPFS	5 MP, 2560 × 1944 resolution Digital WDR 2.8 mm, 3.6 mm, 6 mm fixed focal lens Smart IR, up to 25 m IR distance Audio over coaxial cable, built-in mic 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67,Material	18,370,000	
DS-2CE16H0T-ITFS	5 MP Audio Fixed Mini Bullet Camera 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	20,400,000	

DS-2CE17H0T-IT1F	<p>5 MP Fixed Bullet Camera</p> <p>High quality imaging with 5 MP, 2560 × 1944 resolution</p> <p>Up to 30 m IR distance for bright night imaging</p> <p>One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>Water and dust resistant (IP67)</p> <p>DWDR/BLC/HLC/Global</p>	20,550,000	
DS-2CE17H0T-IT3F	<p>5 MP Fixed Bullet Camera</p> <p>High quality imaging with 5 MP, 2560 × 1944 resolution</p> <p>Up to 40 m IR distance for bright night imaging</p> <p>One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>Water and dust resistant (IP67)</p> <p>DWDR/BLC/HLC/Global</p>	20,610,000	
DS-2CE17H0T-IT3FS	<p>5 MP Audio Fixed Bullet Camera</p> <p>High quality imaging with 5 MP, 2560 × 1944 resolution</p> <p>2.8 mm, 3.6 mm, 6 mm fixed focal lens</p> <p>Up to 40 m IR distance for bright night imaging</p> <p>One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>Water and dust resistant (IP67)</p> <p>High quality audio with audio over coaxial cable, built-in mic</p> <p>DWDR;BLC;HLC;Global</p>	26,350,000	
DS-2CE17H0T-IT5F	<p>5 MP Fixed Bullet Camera</p> <p>High quality imaging with 5 MP, 2560 × 1944 resolution</p> <p>Up to 80 m IR distance for bright night imaging</p> <p>One port for four switchable signals (TVI/AHD/CVI/CVBS)</p> <p>Water and dust resistant (IP67)</p> <p>DWDR/BLC/HLC/Global</p>	Call	
DS-2CE16H0T-IT3ZF	<p>5 MP Bullet Camera</p> <ul style="list-style-type: none"> 5 Megapixel high-performance CMOS Analog HD output, up to 5MP resolution 2.7-13.5mm motorized vari-focal lens True Day/Night OSD menu, 2D DNR, DWDR EXIR technology, up to 40m IR distance IP67 PoC.at Up the Coax(HIKVISION-C) 	Call	
DS-2CE76H0T-ITPF	<p>5 MP turret camera</p> <p>EXIR 2.0: advanced infrared technology with 20 m IR distance</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p> <p>DWDR/BLC/HLC/Global</p>	14,420,000	
DS-2CE76H0T-ITMF	<p>5 MP turret camera</p> <p>EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	18,960,000	
DS-2CE76H0T-ITPFS	<p>5 MP Audio Fixed Turret Camera</p> <p>5 MP coaxial audio camera</p> <p>Enhanced safety with discreet and economical built-in microphone</p> <p>Transmit audio over coaxial cable</p> <p>EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	17,940,000	
DS-2CE76H0T-ITMFS	<p>5 MP Audio Fixed Turret Camera</p> <p>5 MP coaxial audio camera</p> <p>Enhanced safety with discreet and economical built-in microphone</p> <p>Transmit audio over coaxial cable</p> <p>EXIR 2.0: advanced infrared technology with 30 m IR distance</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	21,480,000	
DS-2CE78H0T-IT1F	<p>5 MP turret camera</p> <p>EXIR 2.0: advanced infrared technology with 20 m IR distance</p> <p>Water and dust resistant (IP67)</p> <p>4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)</p>	21,110,000	

DS-2CE78H0T-IT3F	5 MP turret camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	22,810,000	
DS-2CE56H0T-IT1F	5 MP Turret Camera• 5 Megapixel high-performance CMOS• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• True Day/Night • OSD menu, 2D DNR, DWDR• EXIR technology, up to 20m IR distance • IP67 weatherproof• 2560 × 1944 resolution• Up the Coax(HIKVISION-C)	Call	
DS-2CE56H0T-IT3F	5 MP Turret Camera• 5 Megapixel high-performance CMOS• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• True Day/Night • OSD menu, 2D DNR, DWDR• EXIR technology, up to 40m IR distance • IP67 weatherproof• 2560 × 1944 resolution• Up the Coax(HIKVISION-C)	Call	
DS-2CE56H0T-IT3ZF	5MP-Lens: 2.7-13.5mm/F1.2-Horizontal Field of View: 95.7°-29.1°Resolution: 2560x1944px Image sensor: 5 MP CMOS image sensor-Function: day/night ICR-DNR -D-WDR AGC-BLC-Smart IR-Mirror-Min. Illumination: 0.01Lx-IR distans: 40m-Power supply: DC 12VDC Power consumption: max. 6.3W-Dimensions: 123.86x134.3x110.11mm Weight: 580g-Temperature of work: -40°C~60°C	Call	
Turbo HD - 8MP			
DS-2CE78U8T-IT3	4K Ultra-Low Light Turret Camera• 8.29 Megapixel high-performance CMOS • Ultra-low light• 3840 × 2160 resolution• 2.8 mm, 3.6 mm, 6 mm fixed focal lens• 120 dB true WDR, 3D DNR• EXIR 2.0, smart IR, up to 60m IR distance • IP67• Up the Coax(HIKVISION-C)	56,500,000	
DS-2CE18U8T-IT3	K Ultra-Low Light Bullet Camera• 8.29 Megapixel high-performance CMOS • Ultra-low light• 3840 × 2160 resolution• 2.8 mm, 3.6 mm, 6 mm fixed focal lens • 120 dB true WDR, 3D DNR• EXIR 2.0, smart IR, up to 60m IR distance	Call	
Turbo HD DVR (HQHI)			
DS-7204HQHI-K1	4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,CH01: 3MP @ 15fps, CH02-04:1920x1080P @15 fps/ch, support CVBS output, standalone 1U case	Call	
IDS-7204HQHI-M1/S	4 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 6 network cameras can be connected.	41,150,000	
DS-7208HQHI-K1	8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,CH01 & 02: 3MP @ 15fps, CH03-08:1920x1080P @15 fps/ch, , support CVBS output, standalone 1U case	Call	
IDS-7208HQHI-M1/S	8 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 12 network cameras can be connected.	55,360,000	

DS-7116HQHI-K1	<ul style="list-style-type: none"> Support H.265 Pro+/H.265 Pro/H.265 video compression Support HDTV/AHD/CVI/CVBS/IP video input Audio via coaxial cable Max. 6/12/24 IP cameras input (up to 6 MP) Max. 800 m for 1080p and 1200 m for 720p HDTV signal transmission <ul style="list-style-type: none"> Up to 6TB capacity per HDD 	Call	
DS-7216HQHI-K1	16 Turbo HD/AHD/Analog interface input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01-04: 3MP @ 15fps, CH05-16:1920x1080P @15 fps/ch, 4K UHD output , support CVBS output, standalone 1U case	107,750,000	
DS-7216HQHI-K2	16-ch 1080p 1U H.265 POC DVR 16 channels and 2 HDDs 1U DVR Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 24 network cameras can be connected Transmits both HDTV video and power over the same coaxial cable	Call	
iDS-7216HQHI-M2/S	16-ch 1080p 1U H.265 AcuSense DVR 16 channels and 2 HDDs 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 8 network cameras can be connected	133,710,000	
DS-7232HQHI-K2	32 Turbo HD/AHD/Analog interface input -H.265+/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras - Self-adaptive HDTV/HDCVI/AHD/CVBS signal input - Connectable to H.265+/H.265/H.264+/H.264 IP cameras - Full channel recording at up to 4 MP lite resolution - HDMI output at up to 4K (3840 x 2160) resolution - Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal -16-ch synchronous playback	236,480,000	
Turbo HD DVR (HUHI)			
DS-7204HUHI-K1	4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch , alarm I/O: 4/1, support CVBS output, standalone 1U case	59,900,000	
iDS-7204HUHI-M1/S	4 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 8 network cameras can be connected.	56,330,000	
iDS-7208HUHI-M1/S	8 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 16 network cameras can be connected.	106,700,000	
DS-7208HUHI-K1	8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch, 4K UHD output , alarm I/O: 8/4, support CVBS output, standalone 1U case	Call	

<p>DS-7216HUHI-K2</p>	<p>16 Turbo HD/AHD/Analog interface input, 16-ch video&4-ch audio input, 2 SATA interfaces, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, alarm I/O: 16/4, support CVBS output, 380 1U case</p>	<p>193,500,000</p>	
<p>DS-7216HUHI-M2/S</p>	<p>Deep learning-based motion detection 2.0 for all analog channels Deep learning-based perimeter protection Efficient H.265 pro+ compression technology Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/VI/AHD/CVI/CVBS/IP) Up to 32 network cameras can be connected</p>	<p>198,240,000</p>	
<p>DS-7316HUHI-F4/N</p>	<p>Supports HD-TVI, AHD, and Analog Cameras Supports Up to 6/10/18-ch 8 MP IP Cameras Transmission Over UTP and Coaxial Cable H.264+ Compression Recording at Up to 3 MP Resolution HDMI 2 Output at Up to 4K (3840 × 2160) Resolution 4/8/16-ch Synchronous Playback Smart Search for Efficient Playback</p>	<p>395,660,000</p>	
<p>Turbo HD DVR Built in PoC Series</p>			
<p>DS-7204HUHI-K1/P</p>	<p>4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, alarm I/O: 4/1, support CVBS output, standalone 1U case, built-in PoC</p>	<p>59,680,000</p>	
<p>DS-7208HUHI-K2/P</p>	<p>8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 2 SATA interfaces, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, alarm I/O: 8/4, support CVBS output, 380 1U case, built-in PoC</p>	<p>Call</p>	
<p>Turbo HD DVR 1080p/3Mp/5Mp / 8MP Built In PoC</p>			
<p>DS-7204HTHI-K1</p>	<p>4-ch, RCA (2.0 Vp-p, 1 KΩ)-4-chBNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection-2-ch-Up to 8 MP resolution,Supports H.265+/H.265/H.264+/H.264 IP cameras-VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz-Video Bit Rate: -32 Kbps to 16 Mbps-Stream Type: VidVideo, Video & Audio, Video & Audio-Two-way Audio: 1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1st audio input)-Audio Output: 1-ch, RCA (Linear, 1 KΩ)-Audio Bit Rate: -64 Kbps</p>	<p>Call</p>	
<p>DS-7208HTHI-K2</p>	<p>4K H265+ TURBO HD DVR-4-ch, RCA (2.0 Vp-p, 1 KΩ)-Video Compression: H.265+/H.265/H.264+/H.264-Analog Video Input: 8-ch,BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection Analog and HD-TVI video input: 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 IP Video Input: 4-ch,Up to 8 MP resolution,Supports H.265+/H.265/H.264+/H.264 IP-Interface Type: 2 SATA interfacesCapacity: Up to 8 TB capacity for each disk-Alarm Input: 8-Alarm Output: 4</p>	<p>Call</p>	