

| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|-----------------------------|---|---|------|
| 1 | DH-PSDW81642ML-A360-D237 |  | <p>8x2MP Multi-Sensor Panoramic + PTZ WizMind Network Camera Panoramic: Eight 1/1.8" 2 Megapixel progressive scan CMOS 2.8mm fixed lens PTZ: One 1/1.8" 2 Megapixel progressive scan CMOS 5.62mm~208mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking Intelligent Function(Tripwire, Intrusion) 2/2 channel Audio In/Out 7/3 channel Alarm In/Out Micro SD memory, IP66, IK10</p> | Call |
| 2 | DH-PSDW8842ML-A180 |  | <p>4x2MP Multi-Sensor Panoramic + PTZ WizMind Network Camera Panoramic: Four 1/1.8" 2 Megapixel progressive scan CMOS 2.8mm fixed lens PTZ: One 1/1.8" 2 Megapixel progressive scan CMOS 5.62mm~208mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking Intelligent Function(Tripwire, Intrusion) 2/2 channel Audio In/Out 7/3channel Alarm In/Out Micro SD memory, IP66, IK10</p> | Call |
| 3 | DH-PSDW83242M-A360-D845L-S3 |  | <p>32 MP Multi-Sensor 360° Panoramic PTZ Hubble WizMind Network Camera Panoramic parameters: 8 × 4 MP 1/1.8" CMOS image sensors. Outputs max. 32 MP (11520 × 2700)@25/30 fps. PTZ parameters: 1 × 8 MP 1/1.8" CMOS image sensors. Outputs max. 8 MP (3840 × 2160)@25/30 fps. PTZ camera: Built-in illuminators (2 × IR and 7 × laser), max. illumination distance: 500 m. PTZ camera: 45x optical zoom, 16x digital zoom. H.265 codec, high compression rate, ultra-low bit rate. Alarm: 7 in, 3 out; audio: 2 in, 2 out; RS-485; BNC; supports max. 512 G SD card. Panoramic network camera: Three switchable intelligent resources Perimeter protection, crowd map, vehicle density. PTZ camera: Three switchable intelligent resources: Perimeter protection, video metadata, face recognition. GPS/BDS positioning.</p> | Call |
| 4 | DH-IPC-PFW83242-A180 |  | <p>4x8MP WizMind Multi-Sensor Panoramic Bullet Network Camera 4 × 8MP, 1/1.8" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800 2.8mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out 2/2 channel Alarm In/Out Max. IR LEDs length 30m Micro SD memory, IP67, IK10, PoE+</p> | Call |
| 5 | DH-IPC-PDBW8840-A180 |  | <p>4x2MP WizMind Multi-Sensor Panoramic Dome Network Camera Four 2MP 1/2.8" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Outputs max. 8MP (4096 × 1800) @30 fps 2.8mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out 2/2 channel Alarm In/Out Max. IR LEDs length 30m Micro SD memory, IP67, IK10, PoE+</p> | Call |














| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|------------------------|---|--|------|
| 6 | DH-IPC-HFW71242H-Z |  | <p>12MP IR Bullet WizMind Network Camera 12MP 1/1.7" CMOS image sensor, high image definition H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832 3.6mm fixed lens Rotation mode, DWDR; 3D NR, HLC, BLC, digital watermarking Perimeter Protection , Face Detection , Video Metadata , ANPR , People Counting , Queue Management 1/1 channel Audio In/Out 3/2 channel Alarm In/Out Max. IR LEDs length 60m Micro SD memory, IP67, IK10,PoE</p> | Call |
| 7 | DH-IPC-HFW5842E-ZE-S3 |  | <p>8MP IR Vari-focal Bullet WizMind Network Camera 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 8MP (3840x2160) @25/30 fps. Built-in IR LED, and the max. illumination distance is 60 m. ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 512 GB Micro SD card, built-in MIC. 12 VDC/PoE power supply; ePoE. IP67 and IK10 protection. SMD 3.0.</p> | Call |
| 8 | DH-IPC-HFW3841T-ZS |  | <p>8MP IR Vari-focal Bullet WizSense Network Camera 8MP, 1/2.8" CMOS image sensor, low illuminance, high image definition H.265 codec, high compression rate, low bit rate ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. Outputs max. 8MP (3840 x 2160) @20 fps (AI function enabled by default) and supports 8MP (3840 x 2160) @25/30 fps (when AI function disabled) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens (3.6mm, 6mm optional) Max. IR LEDs Length 60m Micro SD Memory,IP67,IK10, PoE</p> | Call |
| 9 | DH-IPC-HFW3841E-AS |  | <p>8MP IR Fixed focal Bullet WizSense Network Camera 8MP, 1/2.8" CMOS image sensor, low illuminance, high image definition H.265 codec, high compression rate, low bit rate ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. Outputs max. 8MP (3840 x 2160) @20 fps (AI function enabled by default) and supports 8MP (3840 x 2160) @25/30 fps (when AI function disabled) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens (3.6mm, 6mm optional) Max. IR LEDs Length 30m, built-in Mic Micro SD Memory,IP67,IK10, PoE</p> | Call |
| 10 | DH-IPC-HFW3849T1-AS-PV |  | <p>8MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. Outputs max. 8 MP (3840 x2160)@25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m. Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built-in dual MICs; 1-ch speaker; support two-way talk. 12 VDC/PoE power supply, IP67 protection. Sound and light alarm (red and blue lights), SMD 4.0. Supports AI SSA and one-tap arming and disarming. SMD area can be set in warm light areas that support triggering alarms.</p> | Call |







NEW

| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|---------------------------|---|---|------|
| NEW | | | | |
| | TIOC 2.0 | | | |
| 11 | DH-IPC-HFW3549T1-AS-PV-S3 |  | <p>SMP Smart Dual Illumination Active Deterrence Fixed-focal Bullet WizSense Network Camera</p> <p>5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <p>Outputs max. 5 MP (2592 × 1944)@20 fps and supports 4 MP (2688 × 1520)@25/30 fps</p> <p>H.265 codec, high compression rate, ultra-low bit rate.</p> <p>Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m.</p> <p>ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments.</p> <p>Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.</p> <p>Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built-in dual MICs; 1-ch speaker; support two-way talk.</p> <p>12 VDC/PoE power supply, IP67 protection.</p> <p>Sound and light alarm (red and blue lights).</p> <p>One-tap arming/disarming through alarm input</p> | Call |
| NEW | | | | |
| | TIOC 2.0 | | | |
| 12 | DH-IPC-HFW3549E-AS-LED |  | <p>SMP Full-color Fixed-focal Warm LED Bullet WizSense Network Camera</p> <p>5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</p> <p>Outputs max. 5MP (2592 × 1944) @20 fps, and supports 4MP (2688 × 1520) @25/30 fps</p> <p>H.265 codec, high compression rate, low bit rate</p> <p>Built-in warm light, max. illumination distance: 30 m</p> <p>ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</p> <p>Alarm: 1 in, 1 out; Audio: 1 in, 1 out; supports max. 256 G Micro SDcard, built-in Mic</p> <p>12V DC/PoE power supply, easy for installation</p> <p>IP67 protection</p> | Call |
| NEW | | | | |
| | TIOC 2.0 | | | |
| 13 | DH-IPC-HFW3549T1-ZAS-PV |  | <p>SMP Smart Dual Light Active Deterrence Vari-focal Bullet WizSense Network Camera</p> <p>5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <p>Outputs max. 5 MP (2960 × 1668) @20 fps and supports 4 MP (2688 × 1520) @25/30 fps</p> <p>H.265 codec, high compression rate, ultra-low bit rate.</p> <p>Built-in warm light and IR LED; the max. IR illumination distance is 50 m and warm light distance is 40 m.</p> <p>ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments.</p> <p>Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built-in dual MICs; 1-ch speaker; support two-way talk.</p> <p>12 VDC/PoE power supply, IP67 protection.</p> <p>Sound and light alarm (red and blue lights).</p> <p>One-tap arming/disarming through alarm input</p> | Call |
| NEW | | | | |
| | TIOC 2.0 | | | |
| 14 | DH-IPC-HFW3449E-AS-LED |  | <p>4MP Full-color Warm LED Fixed-focal Bullet WizSense Network Camera</p> <p>4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</p> <p>Outputs max. 4MP (2688 × 1520) @ 30 fps</p> <p>H.265 codec, high compression rate, low bit rate</p> <p>Built-in Warm LED, max. LED distance: 30 m</p> <p>Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</p> <p>Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic</p> <p>12V DC/PoE power support</p> <p>IP67 protection, SMD Plus</p> | Call |
| NEW | | | | |
| | TIOC 2.0 | | | |
| 15 | DH-IPC-HFW2849T-AS-IL |  | <p>8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera</p> <p>8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <p>Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps..</p> <p>H.265 codec, high compression rate, ultra-low bit rate.</p> <p>Built-in warm light and IR LED, the max. IR light distance is 60 m and max. warm light is 50 m.</p> <p>Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.</p> <p>Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built in MIC.</p> <p>12 VDC/PoE power supply, easy for installation.</p> <p>IP67, IK10 (optional) protection, SMD Plus.</p> | Call |








| ردیف | مدل | تصویر | مشخصات | قیمت | |
|------|---------------------|---|---|--|------|
| 16 | DH-IPC-HFW2531SP-S2 |  | <p>5MP Lite IR Fixed-focal Bullet Network Camera</p> <p>5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</p> <p>Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps</p> <p>H.265 codec, high compression rate, ultra-low bit rate</p> <p>25/30fps@1080P(1920×1080)</p> <p>Intelligent detection: Intrusion, tripwire</p> <p>WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC</p> <p>3.6mm fixed lens</p> <p>Supports max. 256 GB Micro SD card,Max IR LEDs Length 30m</p> <p>IP67, PoE</p> | Call | |
| NEW | 17 | DH-IPC-HFW2549T-AS-IL |  | <p>5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera</p> <p>5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <p>Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps.</p> <p>H.265 codec, high compression rate, ultra-low bit rate.</p> <p>Built-in warm light and IR LED, the max. IR light distance is 60 m and max. warm light is 50 m.</p> <p>Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.</p> <p>Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built in MIC.</p> <p>12 VDC/PoE power supply, easy for installation.</p> <p>IP67, IK10 (optional) protectio, SMD Plus.</p> | Call |
| NEW | 18 | DH-IPC-HFW2541T-AS |  | <p>5MP IR Fixed-focal Bullet WizSense Network Camera</p> <p>5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <p>Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps.</p> <p>H.265 codec, high compression rate, ultra-low bit rate.</p> <p>Built-in IR LED, and the max. illumination distance is 80 m.</p> <p>Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.</p> <p>Alarm: 1 in, 1 out; audio: 1 in, 1 out; Supports max. 256 G Micro SD card; built in MIC.</p> <p>12 VDC/PoE power supply, easy for installation.</p> <p>IP67, IK10 (optional) protection, SMD Plus.</p> | Call |
| NEW | 19 | DH-IPC-HFW2541S-S |  | <p>5MP IR Fixed-focal Bullet WizSense Network Camera</p> <p>5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <p>Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps.</p> <p>H.265 codec, high compression rate, ultra-low bit rate.</p> <p>Built-in IR LED, and the max. illumination distance is 30 m.</p> <p>Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.</p> <p>Supports max. 256 G Micro SD card; built in MIC.</p> <p>12 VDC/PoE power supply.</p> <p>IP67 protection, SMD Plus.</p> | Call |
| NEW | 20 | DH-IPC-HFW2441T-ZAS |  | <p>4MP IR Vari-focal Bullet WizSense Network Camera</p> <p>4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image.</p> <p>Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 (2560 × 1440)@25/30 fps.</p> <p>H.265 codec, high compression rate, ultra-low bit rate.</p> <p>Built-in IR LED, and the max. illumination distance is 60 m.</p> <p>Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.</p> <p>Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); supports max. 256 G Micro SD card; built in MIC.</p> <p>12 VDC/PoE power supply, easy for installation.</p> <p>IP67, IK10 (optional) protection, SMD Plus.</p> | Call |
| NEW | 21 | DH-IPC-HFW2841T-AS |  | <p>8MP IR Fixed-focal Bullet WizSense Network Camera</p> <p>8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <p>Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps.</p> <p>H.265 codec, high compression rate, ultra-low bit rate.</p> <p>Built-in IR LED, and the max. illumination distance is 80 m.</p> <p>Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.</p> <p>Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; Supports max. 256 G Micro SD card; built in MIC.</p> <p>12 VDC/PoE power supply, easy for installation.</p> <p>IP67 , IK10 (optional) protectio, SMD Plus.</p> | Call |












| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|--------------------------|---|---|-----------|
| 22 | DH-IPC-HFW2841S-S |  | <p>8MP IR Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in IR LED, and the max. illumination distance is 30 m. Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection. Supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply. IP67 protection, SMD Plus.</p> | Call |
| 23 | DH-IPC-HFW2449M-AS-LED-B |  | <p>4MP Full-color Fixed-focal Bullet Wizsense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. Outputs max. 4 MP (2688× 1520)@20 fps, and supports (2560 × 1440)@25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in warm light and the max. illumination distance is 50 m. Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection. Alarm: 2 in, 2 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built in Mic. 12 VDC/PoE power supply, 12 VDC power output, max. current 165 mA, easy for installation. IP67 protection, SMD Plus.</p> | Call |
| 24 | DH-IPC-HFW3441E-AS |  | <p>4MP IR Fixed focal Bullet WizSense Network Camera 4MP, 1/3" CMOS image sensor, low illumination, high image definition Outputs max. 4MP (2688 × 1520)@30 fps 20fps@4M(2688×1520)&25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Alarm: In, out; Audio: In, out; Supports max. 256 G Micro SD card, built-in Mic lens 3.6mm,Max IR LEDs Length 50m IP67, IK10(optional), PoE</p> | 8,100,000 |
| 25 | DH-IPC-HFW2441T-AS |  | <p>4MP IR Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 (2560 × 1440)@25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in IR LED, and the max. illumination distance is 80 m. ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply, easy for installation. IP67, IK10 (optional) protection.</p> | Call |
| 26 | IPC-HFW2449S-S-IL |  | <p>4MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate. Built-in warm light/IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m. Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply, easy for installation. IP67 protection, SMD Plus.</p> | 5,200,000 |
| 27 | DH-IPC-HFW2439S-SA-LED |  | <p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" CMOS image sensor, low illumination, high image definition H.265 & H.264 dual-stream encoding 20fps@4M(2688×1520)&25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Supports max. 256 GB Micro SD card 3.5 mm fixed lens,Max IR LEDs Length 30m IP57, IK10(optional), PoE</p> | 6,000,000 |








| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|--------------------------|---|---|-----------|
| 28 | DH-IPC-HFW2431SP-S-S2 |  | <p>4MP Lite IR Fixed-focal Bullet Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition Outputs 4MP (2560 × 1440)@25/30fps, Max. supports 4MP (2688 × 1520)@20 fps H.265& H.264 dual-stream encoding 25/30fps@1080P(1920×1080) Intelligent detection: Intrusion, tripwire 120dB WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Supports max. 256 GB Micro SD card,Max IR LEDs Length 30m IP67, PoE</p> | 5,000,000 |
| 29 | DH-IPC-HFW-1439S1P-A-LED |  | <p>4 MP Entry Full-color Fixed-focal Bullet Network Camera 4-MP 1/3" CMOS image sensor, low luminance, and high definition image H.265 codec, high compression rate, ultra-low bit rate Outputs max. 4 MP (2560 × 1440)@25/30 fps Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes Built-in warm light, and the max. illumination distance is 15 m. 12V DC/PoE power support Built-in MIC. IP67</p> | 4500000 |
| 30 | DH-IPC-HFW1431SP |       | <p>1/3" 4Megapixel progressive CMOS H.265 & H.264 dual-stream encoding 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6 mm fixed lens Max IR LEDs Length 30m IP67, PoE</p> | 4,800,000 |
| 31 | DH-IPC-HFW2239S-SA-LED |   | <p>2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 2MP (1920 × 1080) @25/30 fps ROI, SMART H.264+/H.265+, flexible coding, applicable to various 25/30fps@1080P(1920×1080) 120dB WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS Built-in warm lights, max. illumination distance: 30 m Max IR LEDs Length 30m IP67, PoE</p> | 4,100,000 |
| 32 | DH-IPC-HFW2249S-S-IL |  | <p>NEW</p> <p>2MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 2 MP (1920 × 1080)@25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in warm light/IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m. Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). Supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply, easy for installation. IP67 protection, SMD Plus.</p> | 4,500,000 |
| 33 | DH-IPC-HFW2231SP-S |  | <p>2MP Lite IR Fixed-focal Bullet Network Camera 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 2MP (1920 × 1080) @25/30 fps ROI, SMART H.264+/H.265+, flexible coding, applicable to various 25/30fps@1080P(1920×1080) Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes 3.6 mm fixed lens Max IR LEDs Length 30m IP67, PoE</p> | 3,500,000 |
| 34 | DH-IPC-HFW1230S1-S5 |  | <p>2MP Entry IR Fixed-Focal Bullet Network Camera 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p> | 2,850,000 |

| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|--------------------------|---|--|-----------|
| 35 | DH-IPC-HFW1230SP |  | <p>1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p> | 3,000,000 |
| 36 | DH-IPC-HFW123951P-LED-S4 |  | <p>2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition H.265& H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6 mm fixed lens Max IR LEDs Length 30m IP67, PoE</p> | 3,200,000 |
| 37 | DH-IPC-HDBW7842E1-Z4-X |  | <p>8MP IR Dome WizMind Network CAMERA 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 8 MP (3840 × 2160)@50/60 fps. Built-in IR LED, and the max. illumination distance is 80 m. ROI, flexible coding, applicable to various bandwidth and storage environments. · Two intelligent functions can be enabled at the same time, such as face recognition+people counting, face detection+people counting and PPE Detection+IVS. Built-in Hi-Fi large-diameter speaker covers an auditory range of 20 meters. Sound Management: With its built-in dual MICs and Dahua noise reduction algorithms, the camera supports the sound management function, using it to collect vocals, adaptively reduce noise, and filter non-human voices. Alarm: 3 in, 2 out; audio: 1 in, 1 out; RS-485; BNC; supports max. 512 G Micro SD card. Built-in dual MICs; 1-ch speaker; support two-way talk. 12 VDC/24VAC/PoE+ (802.3at)/ePoE power supply, 12 VDC power output, max. current 165 mA and peak current is 700 mA, easy for installation. IP67 and IK10 protection, Anti-Corrosion coating (optional).</p> | Call |
| 38 | DH-IPC-HDW3841EM-AS |  | <p>8MP IR Fixed focal Eyeball WizSense Network Camera 8MP, 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 8MP (3840 × 2160) @20 fps (AI function enabled by default) and supports 8MP (3840 × 2160) @25/30 fps (when AI function disabled) H.265&H.264 triple-stream encoding ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 3.6mm fixed lens Built-in Mic Max. IR LEDs Length 30m Micro SD memory, IP67, PoE</p> | Call |
| 39 | DH-IPC-HDW3541T-ZAS |  | <p>5MP IR Vari-focal Eyeball WizSense Network Camera 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition Outputs max. 5MP (2592 × 1944) @20 fps, and supports 4MP (2688 × 1520) @25/30 fps H.265&H.264 triple-stream encoding ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 3.6mm fixed lens Built-in Mic Max. IR LEDs Length 40m Micro SD memory, IP67, PoE</p> | Call |
| 40 | DH-IPC-HDW3541TM-AS |  | <p>5MP IR Fixed focal Eyeball WizSense Network Camera 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition Outputs max. 5MP (2592 × 1944) @20 fps, and supports 4MP (2688 × 1520) @25/30 fps H.265&H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) Smart detection supported WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC 2.8mm fixed lens (3.6mm optional) Built-in Mic Max. IR LEDs Length 50m Micro SD memory, IP67, PoE</p> | Call |

| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|--------------------------|---|---|-----------|
| NEW | 41 DH-IPC-HDW2849TM-S-IL |  | <p>8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m. Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection. Supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply, easy for installation. IP67 protection, SMD Plus.</p> | Call |
| NEW | 42 DH-IPC-HDW2441T-AS |  | <p>4MP IR Fixed-focal Eyeball WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in IR LED, and the max. illumination distance is 30 m. ROI, SMART H.264 +/H.265+, flexible coding, applicable to various bandwidth and storage environments. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply. IP67 protection.SMD Plus</p> | 5,000,000 |
| | 43 DH-IPC-HDW2431T-AS-S2 |        | <p>4MP Starlight IR Eyeball Network Camera 1/3" CMOS image sensor, low illumination, high image definition H.265&H.264 Two-stream encoding ,ROI 20fps@4Mp(2688×1520) Smart Detection :Tripwire, Intrusion WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens Max. IR LEDs Length 30m Micro SD memory 256GB,built-in Mic IP67, DC 12 V,PoE</p> | 5,200,000 |
| NEW | 44 IPC-HDBW2441R-ZS |  | <p>4MP IR Vari-focal Dome WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 (2560 × 1440)@25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in IR LED, and the max. illumination distance is 40 m. Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection. Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply, easy for installation. IP67 and IK10 protection, SMD Plus.</p> | Call |
| | 45 DH-IPC-HDW1431T1P-S4 |  | <p>4MP Entry IR Fixed-focal Eyeball Network Camera 4MP, 1/3" CMOS image sensor, low illumination, high image definition Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps H.265 codec, high compression rate, ultra-low bit rate DWDR, Day/Night(ICR), 3DNR, HLC, AGC, BLC Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access Max IR LEDs Length 30m 12V DC/PoE power support, IP67</p> | 4,000,000 |
| | 46 DH-IPC-HDW1431S-S4 |  | <p>4MP Entry IR Fixed-focal Eyeball Network Camera 4MP, 1/3" CMOS image sensor, low illumination, high image definition H.265 & H.264 dual-stream encoding 20fps@4M(2688×1520)&25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card slot, up to 128GB 3.6mm fixed lens Max IR LEDs Length 30m IP67, IK10, PoE</p> | 4,000,000 |








| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|------------------------|---|---|-----------|
| 47 | DH-IPC-HDW3441TM-AS |  | <p>4MP IR Fixed focal Eyeball WizSense Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition Outputs max. 4MP (2688 × 1520) @30 fps H.265& H.264 dual-stream encoding 25/30fps@1080P(1920×1080) Rotation mode,WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, Supports max. 256 G Micro SD card, built-in Mic 3.6mm fixed lens Max IR LEDs Length 50m IP67, PoE</p> | 8,500,000 |
| 48 | DH-IPC-HDW2439T-AS-LED |  | <p>Full-Color 4MP Lite Full-color Fixed-focal Eyeball Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP H.265& H.264 dual-stream encoding Rotation mode,WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Supports max. 256 GB Micro SD card and built-in Mic Built-in warm lights, max. illumination distance: 30 m Max IR LEDs Length 30m IP67, PoE</p> | 6,000,000 |
| 49 | DH-IPC-HDW2449T-S-IL |  | <p>NEW 4MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate. Built-in warm light/IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m. Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). Supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply, easy for installation. IP67 protection,SMD Plus.</p> | 5,200,000 |
| 50 | DH-IPC-HDW2239T-AS-LED |  | <p>Full-Color 2MP Lite Full-color Fixed-focal Eyeball Network Camera 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 2MP (1920 × 1080) @25/30 fps H.265& H.264 dual-stream encoding Rotation mode,WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Supports max. 256 GB Micro SD card and built-in Mic Built-in warm lights, max. illumination distance: 30 m Max IR LEDs Length 30m IP67, PoE</p> | 4,100,000 |
| 51 | DH-IPC-HDW2249T-S-IL |  | <p>NEW 2MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 2 MP (1920 × 1080)@25/30 fps. H.265 codec, high compression rate, ultra-low bit rate. Built-in warm light/IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 M. Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). Supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply, easy for installation. IP67 protection, SMD Plus.</p> | 4,500,000 |
| 52 | DH-IPC-HDW2231T-AS-S2 |  | <p>2MP Lite IR Fixed-focal Eyeball Network Camera 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 2MP (1920 × 1080) @25/30 fps 25/30fps@1080P(1920×1080) 120dB WDR, Day/Night(ICR), 3DNR, HLC, AGC, BLC Supports max. 256 GB Micro SD card, built-in Mic 2.8 mm fixed lens Max IR LEDs Length 30m IP67, PoE</p> | 4,500,000 |
| 53 | DH-IPC-HDW1230T1-S5 |  | <p>2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p> | 2,850,000 |

| رقم | مدل | تصوير | مشخصات | قيمت |
|-----|---------------------|--|---|-----------|
| 54 | IPC-HDW1230T1P-A-S4 |  | <p>2 MP Entry IR Fixed-focal Eyeball Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image H.265 codec, high compression rate, ultra-lowbit rate. Outputs max. 2 MP (1920 × 1080)@25/30 fps DWDR, Day/Night(ICR), 3DNR, HLC, AGC, BLC Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access Max IR LEDs Length 30m 12V DC/PoE power support Built-in MIC, IP67</p> | 3,200,000 |
| 55 | DH-IPC-HDW1230SP |      | <p>2MP IR Eyeball Network Camera 1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p> | 3,000,000 |
| 56 | DH-SD8C848PA |  | <p>8M 48x Starlight IR WizMind Network PTZ Camera 1/1.8" 8Megapixel STARVIS™ CMOS 48x optical zoom Starlight technology Max. 25/30 fps@8M IR distance up to 250 m H.265 encoding, Two-way audio IR and white light, three night view modes IP67, Auto-tracking Perimeter protecton, Face recogniton</p> | Call |
| 57 | DH-SD5A232XA-HNR |  | <p>2MP 32x Starlight IR WizSense Network PTZ Camera H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.9 mm-156 mm Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out Audio 1/1 in/out Support PoE+ IR Distance up to 150m IP66,OSD</p> | Call |
| 58 | DH-SDT4E425-4F |   | <p>X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera Panorama: 1/2.8" 4Megapixel F1.0 CMOS. Detail: 1/2.8"4Megapixel STARVIS™ CMOS. 25x optical zoom. Max. 25/30fps@4M. IR distance up to 100 m. Auto tracking 3.0. Smart tracking. Perimeter protection. Active deterrence. Smart dual light +.</p> | Call |
| 59 | DH-SD6C3432GB-HNR-A |  | <p>4MP 32 Starlight TiOC NETWORK PTZ CAMERA 1/2.8" 4Megapixel STARVIS™ CMOS. 32× optical zoom. Starlight technology. Max. 25/30 fps@4M. IR distance up to 150 m. Auto-tracking 3.0. Perimeter protection. Face detection. SMD 4.0. Full-color illuminator; red and blue warning light. IP66. PoE (802.3at).</p> | Call |

| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|----------------------|---|---|-----------|
| 60 | DH-SD5A232XB-HNR |  | <p>2MP 32xStarlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS Powerful 32x optical zoom Max. 25/30 fps@2M IR distance up to 150 m Deep-learning-based auto tracking and perimeter protection SMD PLUS PoE+ IP67, IK10 Face Detection</p> | Call |
| 61 | DH-SD5A225XA-HNR |  | <p>2MP 25x Starlight IR WizSense Network PTZ Camera H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.9 mm-156 mm Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection) Support Defog and EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out Audio 1/1 in/out Support PoE+ IR Distance up to 150m IP66, OSD</p> | Call |
| 62 | DH-IPC-SD49225XA-HNR |  | <p>2MP 25x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel Starvis Focal Length 4.8mm~120mm 1080P(1920×1080)/720P(1280×720)/ D1(704×576/704×480)/CIF(352×288/352×240) Powerful 25x optical zoom Starlight technology Support H.265&H.264 Triple-streams encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P IVS(Optional) Support PoE+ IR distance up to 100m IP66</p> | Call |
| | |  | | |
| 63 | DH-NVR4108HS-4KS3 |  | <p>8CH Compact 1U 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. Max. decoding capability: 8 × 1080p@30 fps. Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth. Supports IP cameras with a resolution up to 12 MP. AI by Recorder supports 4-channel SMD Plus. AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map. Supports EPTZ, and one-click arming and disarming.</p> | Call |
| 64 | DHI-NVR4108HS-4KS2/L |  | <p>8 Channel Compact 1U 1HDD NVR Access Channel 8 Smart H.265+/ Smart H.264+ Network bandwidth : Access: 80 Mbps; Storage: 80 Mbps; Forward: 60 Mbps Resolution: 8MP; 6MP; 5MP; 4MP; 3MP; 1080p; 720p; D1 Multi-screen Display: 1, 4, 8 views Max. decoding capability: 8 × 1080p@30 fps Multi-channel Playback Up to 8 channels AI : Face detection 4 CH, perimeter protection, IVS, people counting, heat map, and SMD Supports mainstream cameras of ONVIF and RTSP protocols HDD 1 SATA ports, up to 10 TB P2P remote surveillance, video play on mobile device VGA (1920X1080) /HDMI(4K) simultaneous video output Audio Input 1, Audio output 1 Network 1 × RJ-45, 10/100Mbps self-adaptive Ethernet port USB 2 (1 × front USB2.0; 1 × back USB2.0) Supports remote configuration and management of IPC</p> | 7,000,000 |
| | |  | | |

| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|---------------------|---|--|------------|
| 65 | NVR4108HS-EI |  | <p>8CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. Access, storage or forwarding at 80 Mbps. Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding. AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus. AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map. Connected to the third-party network cameras. Security baseline 2.3.</p> | 7,900,000 |
| 66 | DH-NVR4116HS-4KS3 |  | <p>16CH Compact 1U 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps. Max. 160/160/80 Mbps incoming/recording/outgoing bandwidth. Supports IP cameras with a resolution up to 12 MP. AI by Recorder supports 4-channel SMD Plus. AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map. Supports EPTZ, and one-click arming and disarming.</p> | Call |
| 67 | DH-NVR4116HS-4KS2/L |  | <p>16 Channel Compact 1U 1HDD Network Video Recorder H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches New 4.0 user interface. Security baseline 2.1</p> | 9,200,000 |
| 68 | DH-NVR4216-4KS3 |  | <p>16CH 1U 2HDDs Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps. Max. 160/160/80 Mbps incoming/recording/outgoing bandwidth. Supports IP cameras with a resolution up to 12 MP. AI by Recorder supports 4-channel SMD Plus. AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map. Supports EPTZ, and one-click arming and disarming.</p> | Call |
| 69 | DHI-NVR4216-4KS2/L |  | <p>16 Channel 1U 2HDD NVR Access Channel 16 Smart H.265+/ Smart H.264+ Network bandwidth : Access: 160 Mbps; Storage: 160 Mbps; Forward: 64 Mbps Resolution: 8MP; 6MP; 5MP; 4MP; 3MP; 1080p; 720p; D1 Multi-screen Display:1 , 4, 8,16 views Max. decoding capability: 8 × 1080p@30 fps Multi-channel Playback Up to 16 channels AI : Face detection 4 CH, perimeter protection 8 CH, IVS, people counting, heat map, and SMD 12 CH Supports mainstream cameras of ONVIF and RTSP protocols HDD 2 SATA ports, up to 10 TB for a single HDD P2P remote surveillance, video play on mobile device VGA (1920X1080) /HDMI(4K) simultaneous video output Audio Input 1, Audio output 1 , Alarm Input 4 , Alarm Output 2 Network 1 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port USB 2 (1 × front USB2.0; 1 × back USB2.0) Supports remote configuration and management of IPC</p> | 11,000,000 |



| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|--------------------|---|---|------------|
| 70 | DHI-NVR4216-4KS2 |   | <p>16 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card P2P support</p> | 9,500,000 |
| 71 | DH-NVR5216-EI |  | <p>16 Channels 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. Max. decoding capability: 32 × 1080p@30 fps or 16 × 4MP@30 fps. Max. 384 Mbps incoming/recording/outgoing bandwidth. Support AcuPick with Max. 16-Channel. Support N+M cluster. AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. Security baseline 2.3</p> | Call |
| 72 | DHI-NVR5216-4KS2 |   | <p>16 Channel 1U 4K&H.265 Pro Network Video Recorder H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback HDMI/VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera 2 SATA III Ports, up to 8TB capacity for each HDD 2 ports (1 Rear USB3.0,1 Front USB2.0)</p> | Call |
| 73 | DH-NVR4232-4KS3 |  | <p>32CH 1U 2HDDs Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps. Max. 160/128/60 Mbps incoming/recording/outgoing bandwidth. Supports IP cameras with a resolution up to 12 MP. AI by Recorder supports 2-channel SMD Plus. AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map. Supports EPTZ, and one-click arming and disarming.</p> | Call |
| 74 | DHI-NVR4232-4KS2/L |   | <p>32 Channel 1U 2HDD NVR Access Channel 32 Smart H.265+/ Smart H.264+ Network bandwidth : Access: 160 Mbps; Storage: 128 Mbps; Forward: 48 Mbps Resolution: 8MP; 6MP; 5MP; 4MP; 3MP; 1080p; 720p; D1 Multi-screen Display:1 , 4 , 8,16,25,32 views Max. decoding capability: 8 × 1080p@30 fps Multi-channel Playback Up to 16 channels AI : Face detection 4 CH, perimeter protection 8 CH, IVS, people counting, heat map, and SMD 8 CH Supports mainstream cameras of ONVIF and RTSP protocols HDD 2 SATA ports, up to 10 TB for a single HDD P2P remote surveillance, video play on mobile device VGA (1920X1080) /HDMI(4K) simultaneous video output Audio Input 1, Audio output 1 , Alarm Input 4 , Alarm Output 2 Network 1 × RJ-45, 10/100/10000 Mbps self-adaptive Ethernet port USB 2 (1 × front USB2.0; 1 × back USB2.0) Supports remote configuration and management of IPC</p> | 17,000,000 |
| 75 | DH-NVR5232-EI |  | <p>32 Channels 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps. Max. 384 Mbps incoming/recording/outgoing bandwidth. Support AcuPick with Max. 16-Channel. Support N+M cluster. AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. Security baseline 2.3.</p> | 26,000,000 |

| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|--------------------|---|---|------------|
| 76 | DHI-NVR5232-4KS2 |   | 32 Channel 1U 4K&H.265 Pro Network Video Recorder H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback HDMI/VGA simultaneous video output 3D intelligent positioning with Dahua PTZ camera 2 SATA III Ports, up to 8TB capacity for each HDD 2 ports (1 Rear USB3.0,1 Front USB2.0) | 20,000,000 |
| 77 | DH-NVR5432-EI |  | 32 Channels 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps. Max. 384 Mbps incoming/recording/outgoing bandwidth. Support AcuPick with Max. 16-Channel. Support N+M cluster. AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. Security baseline 2.3. | 35,500,000 |
| 78 | DHI-NVR5432-4KS2 |   | 32 channel IPC input 32 channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback Max 16ch@1080P H.265/H.264 decoding 2HDMI/VGA simultaneous video output Support 4 SATA HDDs up to 24TB, 3 USB(1 USB3.0, 2USB2.0) 2*1000 Mbps Network Card RS232 16 Alarm In , 6 Relay Output P2P Support | 30,000,000 |
| 79 | DH-NVR5464-EI |  | 64 Channels 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps. Max. 384 Mbps incoming/recording/outgoing bandwidth. Support AcuPick with Max. 16-Channel. Support N+M cluster. AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. Security baseline 2.3. | Call |
| 80 | DH-NVR5864-EI |  | 64 Channels 2U 8HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps. Support AcuPick with Max. 16-Channel. Support N+M cluster. Support Raid0/1/5/6/10. Max. 384 Mbps incoming/recording/outgoing bandwidth. AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting. Security baseline 2.3. | Call |
| 81 | DHI-NVR608-32-4KS2 |  | 32 Channel Ultra 4K H.265 Network Video Recorder Intel Processor Max 32 IP Camera Inputs Max 384Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback 8SATA Port 8TB Capacity Alarm In/Out: 16/8, 2RJ45(10,100,1000 Mbps) 2HDMI , 1 VGA, 1 eSATA, 4 USB Supports RAID 0/1/5/6/10 Smart Tracking and Intelligent Video | Call |

| ردیف | مدل | تصویر | مشخصات | قیمت |
|------|--------------------|---|---|------------|
| 82 | DHI-NVR608H-32-XI |  | <p>32 Channels 2U 8HDDs WizMind Network Video Recorder 32-channel 1080p self-adaptive decoding capability. Max. 1024/1024/800Mbps incoming/recording/outgoing bandwidth. Supports N+M cluster. Support Raid0/1/5/6/10. Drawer-like chassis design allows for HDD hot swapping. AI by recorder: 4-channel face detection and recognition; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting. HDD 8 SATA ports, up to 16 TB</p> | Call |
| 83 | DHI-NVR608-64-4KS2 |  | <p>64 Channel Ultra 4K H.265 Network Video Recorder Intel Processor Max 64 IP Camera Inputs Max 384Mbps Incoming Bandwidth Up to 12MP Resolution for Preview and Playback 8SATA Port 8TB Capacity Alarm In/Out: 16/8, 2RJ45(10,100,1000 Mbps) 2 HDMI, 1 VGA, 1 eSATA, 4 USB Supports RAID 0/1/5/6/10 Smart Tracking and Intelligent Video</p> | Call |
| 84 | DHI-NVR608H-64-XI |  | <p>64 Channels 2U 8HDDs WizMind Network Video Recorder 32-channel 1080p self-adaptive decoding capability. Max. 1024/1024/800Mbps incoming/recording/outgoing bandwidth. Supports N+M cluster. Support Raid0/1/5/6/10. Drawer-like chassis design allows for HDD hot swapping. AI by recorder: 4-channel face detection and recognition; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting. HDD 8 SATA ports, up to 16 TB</p> | Call |
| | | | | قیمت هر به |
| 85 | DH-PFM920I-6UN-C |  | <p>UTP CAT6 Cable 305 m UTP CAT6, Network Cable CAT 6 / CAT6 UTP LAN Internet Ethernet For CCTV Installation POE High-purity oxygen-free copper conductor Conductor Material: Oxygen free copper (99.97% purity) Diameter: 0.53 mm ± 0.01 mm Insulation Material: HDPE Min Average Thickness: 0.21 mm Diameter: 0.95 mm ± 0.1 mm</p> | Call |
| 86 | DH-PFM920I-6U-U |  | <p>UTP CAT6 Cable 305 m UTP CAT6, Network Cable 24AWG CAT 6 / CAT6 UTP LAN Internet Ethernet For CCTV Installation POE High-purity oxygen-free copper conductor Conductor Material: Oxygen free copper (99.97% purity) Diameter: 0.57 mm ± 0.01 mm American Wire Gauge :23AWG Insulation Material: HDPE Min Average Thickness: 0.21 mm Diameter: 1 mm ± 0.1 mm</p> | Call |

کلیه محصولات با برجسب گارانتی طلایی و کارت گارانتی رستر سرویس ارائه میشود

