Network Camera - NVR			
Items	Description	User Price	
Lite Mini Bullet Series DS-2CD1023G0E-I	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DMR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR	IRR 26,940,000	AMPHIANA .
2 DS-2CD1021G0E-I	(Wide Dynamic Range) - ECO CASE Hikvision 2MP Mini IR Network Bullet camera, 1/2.8" Progressive CMOS, ICR, 1920x1080:20fps (P)/(N), H.265 / H.264 - & H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE Rs. 0.001is our price higher or showing zero? Please chat now and ask for the best price. Prices if shown are inclusive of applicable taxes. Tax rate may be adjusted as per customer's taxation status. For supply of product only, excluding any cabling and/or installation. Shipping charges can sometimes vary.	IRR 13,932,000	
3 DS-2CD1023G0-I	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)	IRR 23,500,000	AMERICAN .
4 DS-2CD1023G0-IUF	High quality imaging with 2 MP resolution, Efficient H.265+ compression technology, Clear imaging against strong back light due to DWDR technology, Water and dust resistant (IP67), EXIR 2.0: advanced infrared technology with long IR range, Support up to 256 GB SD card storage, Built-in microphone for real-time audio security	IRR 40,770,000	per short =
5 DS-2CD1047G0-L ColorVu Lite	4 MP <u>ColorVu Lite</u> Fixed Bullet Network Camera, High quality imaging with 4 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 48,590,000	an
6 DS-2CD1043G0-I	4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 35,160,000	AMERICAN P
7 DS-2CD1057G0-L	5MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 5 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7	IRR 58,820,000	an
8 DS-2CD1053G0-I	5 MP Fixed Bullet Network Camera High quality imaging with 5 MP resolution. Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR ₃ (IP67) EXIR 2.0: advanced infrared technology with long IR range -UF: Bullt-in microphone for real-time audio security	IRR 51,940,000	person a
9 Lite Dome Series			
DS-2CD1323G0E-I	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 29,590,000	No. 10
DS-2CD1323G0-IUF (2.8)	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone	IRR 27,110,000	Transp.
DS-2CD1327G0-L ColorVu	MP <u>ColorVu Lite</u> Fixed Turret Network Camera, High quality imaging with 2 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 35,000,000	ANDERSON .
DS-2CD1347G0-L ColorVu	High quality imaging with 4 MP resolution. Excellent low-light performance.Efficient H.265+ compression technology. Water and dust resistant (IP67). 24/7 colorful imaging.	IRR 81,650,000	anout .
DS-2CD1123G0E-I	2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265+, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 26,360,000	AMADON .
DS-2CD2126G2-ISU 2.8mm	2 MP AcuSense Fixed Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle classification based on deep learning -SU: Built-in microphone for real-time audio security, Audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 81,540,000	
16 DS-2CD2123G2-IU	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 61,350,000	
DS-2CD2125FHWD-IS	2 MP High Frame Rate Fixed Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology High frame rate video to illustrate smooth movement -\$: audio and alarm interface available Water and dust resistant (IPG7) and vandal proof (IK10) Robust structure design with full metal materials.	IRR 49,060,000	
DS-2CD2H25FWD-IZS	2 MP Powered-by-DarkFighter Varifocal Turret Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.2654 compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP66) and vandal proof (IK10) Motorzed varifocal lens for easy installation and monitoring Robust structure design with full metal materials.	IRR 138,870,000	6

			1	
19	DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 41,780,000	
20	DS-2CD1143G0-IUF	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) and vandal resistant (IR10) EXIR 2.0: advanced infrared technology with long IR range Support up to 256 GB SD card storage Built-In microphone for real-time audio security	IRR 49,520,000	
21	DS-2CD1153G0-I	5 MP Fixed Dome Network Camera High qualify limpaing with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) and vandal resistant (IK10) EXIR 2.0: advanced infrared technology with long IR range	IRR 54,540,000	MATERIAL PROPERTY OF THE PROPE
22	Mini Bullet Series			
23	DS-2CD2025FHWD-I		IRR 68,530,000	
24	DS-2CD2021G1-I (2.8)	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Support up to 256 GB SD card storage	IRR 49,980,000	
25	DS-2CD2023G2-I (2.8)	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning	IRR 59,940,000	0-
26	DS-2CD2027G2-L (2.8)	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology 24/7 colorful imaging Focus on human and vehicle classification based on deep learning Water and dust resistant (IP67)	IRR 71,040,000	
27	DS-2CD2043G2-I 2.8mm	4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology -U. Bull-in microphone for real-time audio security Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning	IRR 66,460,000	To are the
28	DS-2CD2043G2-IU (2.8)	4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology -U: Built-in microphone for real-time audio security Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning	IRR 79,110,000	
29	DS-2CD2045FWD-I	4 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal material.	IRR 44,380,000	
	DS-2CD2046G2-I		IRR 70,760,000	
30	DS-2CD2047G2-L (2.8)	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)	IRR 77,730,000	one of
	DS-2CD2085G1-I		IRR 117,160,000	
	DS-2CD2086G2-I		IRR 98,810,000	
31	DS-2CD2063G2-I	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 72,800,000	
32	DS-2CD2083G2-I (2.8)	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 77,710,000	and S

DS-2CD2087G2-LU (2.8MM) Dome Series	4 K Color/u Fixed Bullet Network Camera High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 130 dB WDR technology Focus on human and vehicle classification based on deep learning 24/7 colorful imaging Built-in microphone for real-time audio security (-U)	IRR 156,550,000	(a) 200 (b)
DS-2CD2143G2-IU	4 MP Vandal Built-in Mic Fixed Dome Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology, Efficient H.265+ compression technology, Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning	IRR 66,890,000	
DS-2CD2346G2-IU		IRR 75,130,000	
DS-2CD2347G2-L (2.8)	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning 247 colorful imaging Water and dust resistant (IP67)	IRR 78,910,000	(28)
8 DS-2CD2347G2-LU (2.8)	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)	IRR 89,760,000	
DS-2CD2327G2-L (2.8)		IRR 81,110,000	
DS-2CD1353G0-I (2.8 MM)	5MP Fixed Turret Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range -UF: Built-in microphone for real-time audio security	IRR 52,050,000	(2 B)
11 DS-2CD1357G0-L	5MP ColorVu Lite Fixed Turret Network Camera High quality imaging with 5 MP resolution Excellent low-light performance Efficient H.265+ compression technology Water and dust resistant (IP67) 24/7 colorful imaging	IRR 58,790,000	
DS-2CD2145FWD-IS	4 MP Powered-by-DarkFighter Fixed Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.1265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -S: audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Robust structure design with full metal materials.	IRR 49,060,000	The state of the s
DS-2CD2146G2-I	4 MP AcuSense Fixed Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time auto security(-SU) Water and dust resistant (IP67) and vandal-resistant (IK10)	IRR 49,240,000	THE STATE OF THE S
4 DS-2CD2147G2-LSU (2.8mm)	4 MP Color/u Fixed Dome Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 130 dB WDR technology 24/7 colorful imaging Focus on human and vehicle targets classification based on deep learning -SU: Built-in microphone for real-time audio security, audio and alarm interface available Water and dust resistant (IPG?) and vandal resistant (IRIO)	IRR 85,000,000	ALAUN .
5 DS-2CD2163G2-IU	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP66 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone	IRR 70,780,000	
DS-2CD2166G2-ISU(2.8)		IRR 83,480,000	
16 DS-2CD2166G2-I (2.8mm)	6 MP AcuSense Fixed Dome Network Camera High quality imaging with 6 MP resolution Excellent low-light performance with powered-by-DarKrighter technology Efficient H.266+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security (-SU) Audio and alarm interface available(-SU) Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 53,050,000	Same Comments
47 DS-2CD2183G2-IU	8 MP AcuSense Vandal Fixed Dome Network Camera High quality imaging with 8 MP resolution Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal-resistant (IK10)	IRR 74,280,000	The same of the sa

48	DS-2CD2186G2-I (2.8mm)	4K Acusense Fixed Dome Network Camera High qualify imaging with 8 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security (-SU) Audio and alarm interface available(-SU) Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 65,930,000	
49	DS-2CD2183G0-IS	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5° Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 48,790,000	ALLA O
50	DS-2CD2185FWD-I	4K Fixed Dome Network Camera High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -S: audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Robust structure design with full metal materials.	IRR 108,460,000	
51	Bullet Series			
52	DS-2CD2T43G0-I5	1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265+, H.264+, H.264, Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 46,400,000	5-5
53	DS-2CD2T43G0-I8	1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.118 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.264, H.264, Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 80m IR range	IRR 48,100,000	
	DS-2CD2T43G2-2I (2.8mm)	1/3* Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265+, H.264+, H.264,Three streams,120dB WDR.2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 80m IR range	IRR 66,970,000	
54	DS-2CD2T43G2-2I (4mm)	High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67)21: up to 60 m Focus on human and vehicle targets classification based on deep learning2.8mm	IRR 66,970,000	5-9
55	DS-2CD2T43G2-4I	High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67). 41: up to 80 m Focus on human and vehicle targets classification based on deep learning 4mm	IRR 72,380,000	3-3
56	DS-2CD2T45FWD-I5 lenz4	4 MP Powered-by-DarkFighter Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H. 265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant ([P67) Robust structure design with full metal materials.	IRR 52,170,000	5-0
57	DS-2CD2T45FWD-l82.8mm	4 MP Powered-by-DarkFighter Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials	IRR 124,000,000	6
58	DS-2CD2T46G2-4I (2.8mm)	4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)	IRR 57,190,000	5-0
59	DS-2CD2T46G2-ISU/SL2.8mm	4 MP AcuSense Strobe Light and Audible Warning Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Active strobe light and audio alarm to warn intruders off Provides real-time security via built-in two-way audio Water and dust resistant (IP67)	IRR 60,360,000	5-3
60	Ds-2CD2T47G2-L	4 MP ColorVu Fixed Bullet Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Focus on human and vehicle targets classification based on deep learning 247 colorful imaging Water and dust resistant (IP67)	IRR 95,580,000	
61	DS-2CD2T63G0-I8	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265+, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range	IRR 52,700,000	5-3
62	DS-2CD2T63G2-4I	High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning Water and dust resistant (IP67)	IRR 80,860,000	6
	DS-2CD2066G2-I		IRR 78,390,000	

187 19.					
DS-2CD2T8GQ-4 4-mm	63	DS-2CD2T66G2-2I (2.8mm)	High quality imaging with 6 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning	IRR 58,980,000	5
DB-2CD2T8702-LK 4mm	64	DS-2CD2T66G2-4I 4mm	High quality imaging with 6 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning	IRR 93,180,000	
DS-20027890-88	65	DS-2CD2T87G2-LK 4mm	Efficient II-1265+ compression technology Clear imaging against strong back light due to 130 dB WDR technology Focus on human and vehicle classification based on deep learning	IRR 113,860,000	www.co
DS-2CD2T88G2-41 DS-2CD2T88G2-41 DS-2CD2T88G2-41 DS-2CD2T88G2-41 DS-2CD2T8BG2-41 DS-2CD2TBG2TBG2-41 DS-2CD2TBG2TBG2-41 DS-2CD2TBG2TBG2-41 DS-2CD2TBG2TBG2-41 DS-2CD2TBG2TBG2-41 DS-2CD2TBG2TBG2TBG2TBG2TBG2TBG2TBG2TBG2TBG2TBG	66	DS-2CD2T83G0-I8	fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in	IRR 55,760,000	5-9
Introduction International International		DS-2CD2T85G1-I5		IRR 135,710,000	
DS-2CD2T83G2-41 Cheminary regarded region bedrafty does 10 years provided by Wilder bedrafty (PSP) Cheminary regarded region bedrafty (PSP) Cheminary region by the provided by Wilder and dut resident (PSP) Cheminary region with the PSP residence region by the provided by the		DS-2CD2T85G1-I8		IRR 134,730,000	
Excellent No. Mey Rep Find France (1997) Excellent No. Sept Sept Sept Sept Sept Sept Sept Sept	67	DS-2CD2T83G2-4I	Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning	IRR 93,900,000	6-9
Big Causilly imaging with 8 MF resolution Excellent Investigation Excellent Investigatio	68	DS-2CD2T86G2-4I	Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light by 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)	IRR 120,150,000	
DS-2CD2327WD-1			High quality imaging with 8 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light by 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning	IRR 100,420,000	5-3
DS-2CD2345FWD-I	71		Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment -	IRR 35,500,000	- B
1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - H.265+/H.265H/4.264/M.PEG - IR: up to 10 m 120 dB WDR - Bulli-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2. AGC ON), 0.028 lux @ (F2.0. AGC ON), 0.1 ux with IR - St Bulli-in Micro, audioislarm IO			Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment -	IRR 45,950,000	(F)
DS-2CD2542FWD-IS	74		120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC	call	P ₀
High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Efficient H.265+ compression technology Efficient H.265+ compression technology H.V. W.F. connection -V. W.F. Connection	75	DS-2CD2542FWD-IS	H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC,	call	
2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/RO/1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264-Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	76		High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -W: WI-Fi connection -S: built-in microphone, audio and alarm interface available Water and dust resistant (IP66) and vandal proof (IK08) Mini size suitable for limited space	IRR 49,840,000	D .
DNR/RO/1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H 265+, H 265+, H 264+, H 265, H 264+, H 264-Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Call 4 MP EXIR VF Bullet Network Camera, 1/3* progressive scan CMOS - BLC/3D DNR/ROI - 2560 × 1440@20fps, Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H 265+, H 265+, H 264+, H 264- 1204B True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro	78		2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+,	IRR 43,180,000	6
DS-2CD1643G0-IZ 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265+, H.264+, H.264- 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux@ (F1.6, AGC ON) - Built-in micro	79	DS-2CD1623G0-IZ	DNR/ROI1920 × 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB -	call	100
	80	DS-2CD1643G0-IZ	1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67- H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux@ (F1.6, AGC ON) - Built-in micro	IRR 81,350,000	100

81	DS-2CD1653G0-I	5 MP Varifocal Bullet Network Camera. High quality imaging with 5 MP resolution; Efficient H.265+ compression technology; Clear imaging even with strong	IRR 52,250,000	100
82	Lite Dome Vari-Facal Series			
83	DS-2CD1743G0-IZ	4.0 MP VF Network Dome Camera-1/3* progressive scan CMOS - 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps □ Up to 30 m IR range- 2.8 mm to 12 mm manual/motorized (with - PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264- Dual stream- 120 dB WDR (Wide Dynamic Range) - Z:Motorized VF lens	IRR 91,340,000	
84	DS-2CD1753G0-I	5 MP Varifocal Dome Network Camera High quality imaging with 5 MP resolution,Efficient N.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR, Up to 256 GB memory card slot for storage, 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal proof (IK10), EXIR 2.0: advanced infrared technology with long IR range	IRR 87,000,000	moon .
85	DS-2CD1753G0-IZ	High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Up to 256 GB memory card slot for storage 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring Water and dust resistant (IP67) and vandal proof (IK10) EXIR 2.0: advanced infrared technology with long IR range	IRR 98,470,000	2 00000
86	Bullet Vari-Facal Motorized	I		
87	DS-2CD2625FWD-IZS	2MP Powered by DarkFighter Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by-DarkFighter technology,Efficient H.265+ compression technology,Cleri maging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP66) and vandal proof (IK10), Motorized varifocal lens for easy installation and monitoring full metal materials.	IRR 110,210,000	
88	DS-2CD2632F-I	3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048×1536:25fps(P)/30fps(N), 2.8-12mm VF lens, H.264/MJPEG/H.264+, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 60,500,000	
89	DS-2CD2643G2-IZS	MP WDR Motorized Varifocal Bullet Network Camera, High quality imaging with 4 MP resolution Motorized varifocal lens for easy installation and monitoring Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology,(IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning	IRR 124,710,000	
90	DS-2CD2645FWD-IZS	4 MP Powered-by-DarkFighter Varifocal Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP66) and vandal proof (IK10) Motorized varifocal lens for easy installation and monitoring Robust structure design with full metal materials.	IRR 92,660,000	
91	DS-2CD2663FG0-IZS	6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9° Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - z:Motorized VF lens	call	
	DS-2CD2685G1-IZS		IRR 150,320,000	
92	DS-2CD2683G2-IZS	8 MP AcuSense Motorized Varifocal Bullet Network CameraHigh quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoringEfficient H.265+ compression technology Clear imaging against strong backlight due to 120 d8 true WDR technologyFocus on human and vehicle targets classification based on deep learningAudio and alarm interface availableWater and dust resistant (IP67) and vandal-resistant (IK10)	IRR 139,300,000	
93	DS-2CD2685FWD-IZS	4K Powered-by-DarkFighter Varifocal Bullet Network Camera High quality imaging with 8 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP66) and vandal proof (IK10) Motorized varifocal lens for easy installation and monitoring Robust structure design with full metal materials	IRR 124,080,000	
94	DS-2CD2683G0-IZS	8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0.1 Lux with IR - H.265+, H.265+, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI • IP67, IK10 - Z:Motorized VF lens	call	0-0
95	DS-2CD2686G2-IZS (2.8-12mm)	High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP66) and vandal proof (IK10)	IRR 178,370,000	
96	Dome Vari-Facal Motorized	Series		
97	DS-2CD2743G2-IZS	4 MP Outdoor WDR Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolutionEfficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology-S: audio and alarm interface available-Water and dust resistant (IP67) and vandal proof (IK10)-Motorized varifocal lens for easy installation and monitoring-Robust structure design with full metal materials	IRR 149,000,000	puntary 3
98	DS-2CD2746G2-IZS		IRR 152,400,000	

		4 MP Powered-by-DarkFighter Varifocal Dome Network Camera		
99	DS-2CD2745FWD-IZS	High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP66) and vandal proof (IK10) Motorized varifocal lens for easy installation and monitoring Robust structure design with full metal materials.	IRR 92,660,000	
100	DS-2CD2783G2-IZS	8 MP AcuSense Motorized Varifocal Dome Network Camera High quality imaging with 8 MP resolutionMotorized varifocal lens for easy installation and monitoring Efficient H 265+ compression technology/Clear imaging against strong backlight due to 120 dB true WDR technologyFocus on human and vehicle targets classification based on deep learning Audio and alarm interface availableWater and dust resistant (IP67) and vandal-resistant (IK10)	IRR 137,470,000	Account of the Control of the Contro
101	DS-2CD2763G1-IZS	6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 ×2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Bullt-in micro SD/SDHC/SDXC card slot, up to 128 GB - 2: Motorized VF lens	IRR 142,160,000	name of the same o
102	DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - 1.265+, H.265+, H.264+, H.264 - 1204B WDR - 2 Behavior analyses, and face detectio - BLC/3D DNR/ROI - IP67 - IKT0 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 2: Motorized VF lens	call	Committee of the Commit
	DS-2CD2785G1-IZS		IRR 150,320,000	
103	DS-2CD2786G2-IZS	4K AcuSense Varifocal Dome Network Camera High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP66) and vandal proof (IK10)	IRR 195,970,000	
104	Fish Eye Series			
105	DS-2CD2955FWD-I	5 MP Network Fisheye Camera,Up to 5 megapixel high resolution, 2560 × 1920 @30fps,H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180*, vertical FOV 180*, Dual video streams, DC12V & POE (802.3	IRR 126,380,000	
106	DS-2CD6332FWD-IS	360° zero-blind zone image: a fisheye network camera capable of providing a 360 degree panoramic image of its surveillance scene IP66/IK10 water resistant and vandal proof, preventing water ingress for outdoor use Multi dewarping modes: the image can be dewarped to normal image for viewing intuitively Build-in mic and speaker: the camera supports two-way audio for real-time audio security monitoring and communication Built-in IR light: an IR range of 15 meters provides good visibility in low or even zero-light environments	IRR 178,300,000	
107	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera,Up to 5 megapixel high resolution,2560 × 1920 @30fps,H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3	IRR 102,960,000	0
108	Cube Smart Series			
109	DS-2CD2420F-I(W)	Up to 2 megapixel (1920 × 1080 @ 30 fps) resolution - Standard video compression with high compression ratio, ROI (region of interest) encoding - Progressive scan CMOS - Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB- IR range approx. 10 meters - Two-way audio - Built-in microphone and speaker -Support Wi-Fi, support WPS configuration with one touch - Support PIR(Passive Infrared Detection) - IR cut filter with auto switch - Integrated mount for easy installation, Digital Wide Dynamic Range, Auto-electronic shutter	call	
110	DS-2CD2421G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ DWDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	IRR 28,480,000	
111	DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	call	
112	DS-2CD2443G0-IW	1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR -Video Compression: H.265+/H.265/H.264+/H.264/MJ/PEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	IRR 61,130,000	
113	Pin Hole Series DS-2CD2D14WD 2Q Smart Series	1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B.W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	call	
116	DS-2CD2Q10FD-IW	1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0" - 355", Tilt: -20" - 90	IRR 31,300,000	P
117	2U Smart Series			

118	DS-2CV2U21FD-IW	2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 126GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	IRR 21,790,000	
120	People Counting IDS-2CD6412FWD/C	Minimum Illumination: Color: 0.01 lux @ (f/1.2, AGC on), 0.028 lux @ (f/2.0, AGC on) 1.3 MP (1280 x 960) Resolution Lenses: 2.1 mm or 2.8 mm H.264/MJPEG/MPEG4 Frame Rate: 50 Hz: 25 fps (1280 x 960), (1280 x 720) 12 VDC, 7.5 W	IRR 224,880,000	
121	DS-2DE4A225IW-DE	4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by, DarkFighter technology, Clear imaging against strong back lighting due to 120 dB WDR technology, Pan and tilt ability enables camera to monitor zones of interest, 25x optical zoom allows for closer viewing of subjects in expansive areas, Up to 50m IR range ensures safety at night (IP66)	IRR 124,900,000	
	DS-2SE4C425MWG-E		IRR 320,560,000	
	DS-2SE4C225MWG-E		IRR 281,810,000	
123	DS-2DE4220IW-DE	2MP 20× Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360" endless; Tilt range: -15*~90" (Auto Flip), Pan Speed: 0.1* -80"/s, Tilt Speed: 0.1* -80"/s, 100m IR Distance, POE&12VDC	call	
124	DS-2DE4225IW-DE-T5	2MP 25× Network IR Speed Dome - 1/2.8* progressive scan CMOSUp to 1920 × 1080@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) Lux with IR25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 214,590,000	
125	DS-2DE4425IW-DE T5	4MP 25× Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 2560 × 1440@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) Lux with IR25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 252,150,000	
126	DS-2DE5432IW-AE-S5	5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality meaning with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm Face capture: Up to 5 faces captured at the same time	IRR 229,040,000	
127	DS-2DE5220IW-AE	DS-2DE5220IW-AE 2MP 20× Network IR Speed Dome 2.54cm (17.8") Progressive Scan CMOS Up to 1920 × 1080 resolution 20× Optical Zoom, 16× Digital Zoom Digital WDR 30 intelligent positioning function Up to 150 m IR distance Hi-PoE/24 VAC power supply Support H.265 video compression	IRR 338,660,000	
128	DS-2DE4A320IW-DE	3MP Network IR PTZ Camera 1/2.8" Progressive Scan CMOS Up to 2048 × 1536 resolution 20× Optical Zoom, 16× Digital Zoom WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance 12 VDC & PoE+ (802.3at, class4) Support H.265 video compression	IRR 274,170,000	
129	DS-2DF6A236X-AEL	6-inch 2 MP 36X DarkFighter Network Speed Dome High quality imaging with 2 MP resolution Excellent low-light performance via DarkFighter technology 36x optical zoom provides close up views over expansive areas Intelligent functions based on deep learning Water and dust resistant (IP67) and vandal proof (IK10).	IRR 520,800,000	
	DS-2DE7A432IW-AEB (T5)		IRR 490,000,000	
130	DS-2CDE5432IW-AE	5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8* Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32* optical zoom, 18* digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm Face capture: Up to 5 faces captured at the same time	IRR 229,050,000	
131	DS-2DE5230W-AE	2MP 30× Network IR Speed Dome - 1/2.8° CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	call	

132	DS-2CD5220IW-AE	2MP 20X Network IR PTZ Dome Camera 1920 x 1080, 1/2.8" Progressive Scan CMOS 20X Optical Zoom DWDR 3D intelligent positioning function Support cloud P2P Up to 150m IR distance □ Hi-PoE / /24VAC power supply □ Support BNC output	IRR 231,170,000	
133	DS-2DF5276-AE3	2MP 20× Network Speed Dome , 1/2.8" Progressive Scan CMOS Up to 1920 × 1080 resolution 20× Optical Zoom, 16× Digital Zoom Digital WDR 3D intelligent positioning function 24 VAC & PoE+ (802.3at, class4) Support H.265 video compression	IRR 562,530,000	
134	DS-2DF5276-AEL	1.3MP 30X Network PTZ Dome Camera, 1/3" Progressive Scan CMOS 30X optical zoom, 16X digital zoom Smart Tracking, Defog, ROI encoding, HLC 3-Streams True Day/Night, 3D DNR, Digital WDR 3D intelligent positioning High-PoE / PoE+ / 24VAC power supply	IRR 447,450,000	
135	DS-2DE7232IW-AE	2MP 32× Network IR Speed Dome, Up to 1920 × 1080@60fps resolution,Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON),BW: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR,32× optical zoom, 16× digital zoom, WDR, HLC, BLC, 3D DNR, Defog,EIS,Regional Exposure, Regional Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	call	1.
136	DS-2DF8236I5W-AELW	High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Clear imaging against strong back lighting due to 120 dB WDR technology Pan and tilt ability enables camera to monitor zones of interest 32x optical zoom allows for closer viewing of subjects in expansive areas Up to 150m IR range ensures safety at night Water and dust resistant (IP66).	IRR 1,143,020,000	ST. ST.
138	DS-7600NI-E1/A	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 164,300,000	
140	DS-7104NI-Q1/M	IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 26,860,000	
141	DS-7104NI-Q1	4-ch Mini 1U NVR H.265+/H.265/H.264-/H.264 video compression Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 4-ch network camera inputs Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output	IRR 20,290,000	
142	DS-7104NI-Q1/4P/M	IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
143	DS-7604NI-Q1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
144	DS-7604NI-Q1/4P	IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
145	DS-7604NI-K1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 61,560,000	•
146	DS-7604NI-K1/4P	IP video input : 4-ch - 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 82,740,000	
14/	NVIC O Chailliel			
148	DS-7108NI-Q1/M	IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMl output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 49,380,000	
149	DS-7108NI-Q1/8P/M	IP video input :8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	was painting
150	DS-7608NI-Q2/8P	IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	call	
151	DS-7608NI-Q1	Up to 8-ch IP camers inputs H.255+H.245-H.256 AV (abe formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	IRR 35,500,000	
152	DS-7608NI-Q2	Up to 8-ch IP camera inputs H.265+H.265H.264+H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	IRR 61,800,000	

_				
153	DS-7608NI-K1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 68,340,000	
154	DS-7608NI-K1/8P	8-ch 1U 8 PoE 4K NVR Up to 8-ch IP camera inputs H.265+/H.265H/1-264-video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	IRR 126,190,000	
155	DS-7608NI-K2	8-ch 1U 4K NVR Up to 8-ch IP camera inputs H.265+IH.265+IH.264+IH.264 video formats Up to 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity 1 HDMI and 1 VGA interfaces, both interfaces support independent video outpu 2 SATA interfaces for HDD connection (up to 10 TB capacity per HDD) Up to 80 Mbps incoming bandwidth	IRR 71,200,000	
156	NVR 16 Channel			
157	DS-7616NI-Q1	IP video input: 16-ch Up to 8 MP resolution - Decoding format: H.265+/H.265/ H.264+/H.264 - Incoming bandwidth: 160 Mbps - HDMI output: 4K (3840 × 2160)/30Hz - Capacity: 1 SATA interface Up to 6TB capacity	IRR 48,200,000	No.
158	DS-7616NI-Q2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 89,810,000	
159	DS-7616NI-Q2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265+/H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 107,470,000	
160	DS-7616NI-K1	Up to 16-ch IP camera inputs H.265-/H.2654/H.264-/H.264 video formats Up to 1-ch @ 8MP or 5-ch @ 1080P decoding capacity Up to 160 Mbps incoming bandwidth	IRR 74,000,000	
161	DS-7616NI-K2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 82,970,000	
162	DS-7616NI-K2/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265+/H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 162,340,000	
163	DS-7716NI-Q4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 178,100,000	112
164	DS-7716NI-Q4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMl output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 255,140,000	***
165	DS-7716NI-K4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265+/H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 211,190,000	
166	DS-7716NI-K4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265+/H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	call	
167	Network Video Recorders- Ultra			
168	DS-8616NI-K8	16-ch 2U 4K NVR,Up to 16 channel IP cameras can be connected, Supports decoding H.265+/H.265H.264+/H.264H.264/MPEG4 video formats Up to 4K high-definition live view, storage and playback, Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected,2 HDMI (different source) and 2 VGA (different source) interfaces,8 HDD can be used for continuous video recording, Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera	IRR 147,000,000	
169	NVR 32 Channel			
170	DS-7732NI-Q4	IP video input: 32-ch Up to 8 MP resolution - Decoding format: H.265+/H.265/ H.264+/H.264 - Incoming bandwidth: 200 Mbps - HDMI output: 1920 × 1080/60Hz - Capacity: 4 SATA interface Up to 6TB capacity for each disk	IRR 119,500,000	10 Tes
171	DS-7732NI-Q4/16P	IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H 265+/H.265+/H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 170,000,000	1
172	DS-7732NI-K4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 210,450,000	
173	IDS-7732NXI-I4/8S	32-ch 1.5U 4K DeepinMind NVR H.265-/H.264-/H.264 video formats Intelligent nandytics based on deep learning algorithm Up to 16-ch perimeter protection Up to 8-ch facial recognition for video stream, or up to 16-ch facial recognition for face picture Up to 8-ch video structuralization Up to 8-ch video structuralization Up to 32-ch IP cameras can be connected Up to 16-ch 1080p decoding capability	IRR 719,160,000	1130
174	DS-7732NI-K4/16P	IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265+/H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 334,310,000	
175	DS-8632NI-K8	Up to 32 channel IP cameras can be connected Supports decoding H.265+/H.265H.264+/H.264/MPEG4 video formats Up to 4K high-definition live view, storage and playback Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera	IRR 218,820,000	Acres 1

176	IDS-9632NXI-I8/4F	32-ch 2U 4K DeepinMind NVR H.265+/H.265+/H.264+/H.264 video formats Up to 32 channel IP cameras can be connected 8 HDD can be used for continuous video recording Intelligent analytics based on deep learning algorithm Up to 16-ch perimeter protection Up to 8-ch facial recognition for video stream, or up to 16-0h facial recognition for face picture Up to 4-ch video structuralization Up to 16-ch 1080p decoding capability	IRR 3,213,890,000	
	DS-9632NXI-I8/S		IRR 739,020,000	
177	DS-9632NI-18	32-ch 2U 4K NVR Up to 32 channel IP cameras can be connected Up to 12 MP high-definition live view, storage and playback Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) cameral/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	IRR 626,320,000	
178	DS-9632NI-I16	32-ch 3U 4K NVR Up to 32 channell Pic ameras can be connected Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 16 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) cameral/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	IRR 715,640,000	
179	DS-9664NI-I8	64-ch 2U 4K NVR Up to 64 channel IP cameras can be connected Up to 12 MP high-definition live view, storage and playback Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	IRR 682,530,000	
	DS-9664NXI-18/S		IRR 968,630,000	
	DS-8664NI-I8		IRR 500,000,000	
180	DS-9664NI-I16	64-ch 3U 4K NVR Up to 64 channel IP cameras can be connected Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 16 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	IRR 1,029,160,000	30.